
Subject: i2o: CONFIG_DEBUG_SG compilation fixed
Posted by [vaverin](#) on Mon, 29 Oct 2007 06:32:13 GMT
[View Forum Message](#) <> [Reply to Message](#)

i2o crashed when CONFIG_DEBUG_SG is enabled because i2o_block_request structure includes array of scatterlists that should be initialised

Signed-off-by: Vasily Averin <vvs@sw.ru>

```
--- a/drivers/message/i2o/i2o_block.c
+++ b/drivers/message/i2o/i2o_block.c
@@ -1137,6 +1137,18 @@ static struct i2o_driver i2o_block_driver = {
 *
 * Returns 0 on success or negative error code on failure.
 */
+
+
+#ifdef CONFIG_DEBUG_SG
+static void i2o_block_req_ctor(struct kmem_cache *cachep, void *objp) {
+ sg_init_table(((struct i2o_block_request *) (objp))->sg_table,
+ I2O_MAX_PHYS_SEGMENTS);
+}
+
+#define I2O_BLK_CTOR &i2o_block_req_ctor
+#else
+#define I2O_BLK_CTOR NULL
+#endif
+
static int __init i2o_block_init(void)
{
    int rc;
@@ -1147,7 +1159,7 @@ static int __init i2o_block_init(void)
    /* Allocate request mempool and slab */
    size = sizeof(struct i2o_block_request);
    i2o_blk_req_pool.slab = kmem_cache_create("i2o_block_req", size, 0,
-    SLAB_HWCACHE_ALIGN, NULL);
+    SLAB_HWCACHE_ALIGN, I2O_BLK_CTOR);
    if (!i2o_blk_req_pool.slab) {
        osm_err("can't init request slab\n");
        rc = -ENOMEM;
```
