
Subject: [PATCH 1/5] The config option itself
Posted by [Pavel Emelianov](#) on Wed, 31 Oct 2007 10:06:34 GMT
[View Forum Message](#) <[Reply to Message](#)

The option is called NAMESPACES. It can be selectable only if EMBEDDED is chosen (this was Eric's requisition). When the EMBEDDED is off namespaces will be on automatically.

Signed-off-by: Pavel Emelyanov <xemul@openvz.org>

```
diff --git a/init/Kconfig b/init/Kconfig
index c3de3ed..fc76773 100644
--- a/init/Kconfig
+++ b/init/Kconfig
@@ -400,6 +400,15 @@ config RELAY
```

If unsure, say N.

```
+config NAMESPACES
+ bool "Namespaces support" if EMBEDDED
+ default !EMBEDDED
+ help
+   Provides the way to make tasks work with different objects using
+   the same id. For example same IPC id may refer to different objects
+   or same user id or pid may refer to different tasks when used in
+   different namespaces.
+
config BLK_DEV_INITRD
  bool "Initial RAM filesystem and RAM disk (initramfs/initrd) support"
  depends on BROKEN || !FRV
--
```

1.5.3.4

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
