
Subject: [PATCH 1/5] The config option itself
Posted by [Pavel Emelianov](#) on Wed, 31 Oct 2007 10:06:34 GMT
[View Forum Message](#) <> [Reply to Message](#)

The option is called NAMESPACES. It can be selectable only if EMBEDDED is chosen (this was Eric's requisition). When the EMBEDDED is off namespaces will be on automatically.
Signed-off-by: Pavel Emelyanov <xemul@openvz.org>

```
diff --git a/init/Kconfig b/init/Kconfig
index c3de3ed..fc76773 100644
--- a/init/Kconfig
+++ b/init/Kconfig
@@ -400,6 +400,15 @@ @@ config RELAY
```

If unsure, say N.

```
+config NAMESPACES
+ bool "Namespaces support" if EMBEDDED
+ default !EMBEDDED
+ help
+ Provides the way to make tasks work with different objects using
+ the same id. For example same IPC id may refer to different objects
+ or same user id or pid may refer to different tasks when used in
+ different namespaces.
+
+ config BLK_DEV_INITRD
+   bool "Initial RAM filesystem and RAM disk (initramfs/initrd) support"
+   depends on BROKEN || !FRV
+
--
1.5.3.4
```

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
