
Subject: [PATCH 2/5] Move the UTS namespace under the option
Posted by Pavel Emelianov on Wed, 31 Oct 2007 10:08:46 GMT
[View Forum Message](#) <> [Reply to Message](#)

Currently all the namespace management code is in the kernel/utsname.c file, so just compile it out and make stub in .h file.

The init namespace itself is in init/version.c and is left in the kernel.

Signed-off-by: Pavel Emelyanov <xemul@openvz.org>

```
diff --git a/include/linux/utsname.h b/include/linux/utsname.h
index 923db99..1123267 100644
--- a/include/linux/utsname.h
+++ b/include/linux/utsname.h
@@ -35,6 +35,7 @@ struct new_utsname {
#include <linux/sched.h>
#include <linux/kref.h>
#include <linux/nsproxy.h>
+#include <linux/err.h>
#include <asm/atomic.h>

struct uts_namespace {
@@ -43,6 +44,7 @@ struct uts_namespace {
};
extern struct uts_namespace init_uts_ns;

+#ifdef CONFIG_UTS_NS
static inline void get_uts_ns(struct uts_namespace *ns)
{
    kref_get(&ns->kref);
@@ -56,6 +58,25 @@ static inline void put_uts_ns(struct uts_namespace *ns)
{
    kref_put(&ns->kref, free_uts_ns);
}
+#else
+static inline void get_uts_ns(struct uts_namespace *ns)
+{
+}
+
+static inline void put_uts_ns(struct uts_namespace *ns)
+{
+}
```

```

+static inline struct uts_namespace *copy_utsname(unsigned long flags,
+      struct uts_namespace *ns)
+{
+ if (flags & CLONE_NEWUTS)
+  return ERR_PTR(-EINVAL);
+
+ return ns;
+}
+#endif
+
 static inline struct new_utsname *utsname(void)
 {
  return &current->nsproxy->uts_ns->name;
diff --git a/init/Kconfig b/init/Kconfig
index fc76773..d592aa2 100644
--- a/init/Kconfig
+++ b/init/Kconfig
@@ -409,6 +409,13 @@ config NAMESPACES
    or same user id or pid may refer to different tasks when used in
    different namespaces.

+config UTS_NS
+ bool "UTS namespace"
+ depends on NAMESPACES
+ help
+   In this namespace tasks see different info provided with the
+   uname() system call
+
config BLK_DEV_INITRD
  bool "Initial RAM filesystem and RAM disk (initramfs/initrd) support"
  depends on BROKEN || !FRV
diff --git a/kernel/Makefile b/kernel/Makefile
index 8c99161..8082b2c 100644
--- a/kernel/Makefile
+++ b/kernel/Makefile
@@ -9,7 +9,7 @@ obj-y = sched.o fork.o exec_domain.o panic.o printk.o profile.o \
        rcupdate.o extable.o params.o posix-timers.o \
        kthread.o wait.o kfifo.o sys_ni.o posix-cpu-timers.o mutex.o \
        hrtimer.o rwsem.o nsproxy.o srcu.o \
-       utsname.o pm_qos_params.o notifier.o sysctl_check.o
+       pm_qos_params.o notifier.o sysctl_check.o

obj-$(CONFIG_STACKTRACE) += stacktrace.o
obj-y += time/
@@ -48,6 +48,7 @@ obj-$(CONFIG_AUDITSYSCALL) += auditsc.o
obj-$(CONFIG_AUDIT_TREE) += audit_tree.o
obj-$(CONFIG_KPROBES) += kprobes.o
obj-$(CONFIG_KGDB) += kgdb.o

```

```
+obj-$(CONFIG_UTS_NS) += utsname.o  
obj-$(CONFIG_SYSFS) += ksysfs.o  
obj-$(CONFIG_DETECT_SOFTLOCKUP) += softlockup.o  
obj-$(CONFIG_GENERIC_HARDIRQS) += irq/  
--
```

1.5.3.4

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
