
Subject: [PATCH 3/5] Move the IPC namespace under the option
Posted by [Pavel Emelianov](#) on Wed, 31 Oct 2007 10:10:40 GMT
[View Forum Message](#) <> [Reply to Message](#)

Currently all the IPC namespace management code is in ipc/util.c. I moved this code into ipc/namespace.c file which is compiled out when needed.

The linux/ipc_namespace.h file is used to store the prototypes of the functions in namespace.c and the stubs for NAMESPACES=n case. This is done so, because the stub for copy_ipc_namespace requires the knowledge of the CLONE_NEWIPC flag, which is in sched.h. But the linux/ipc.h file itself is included into many many .c files via the sys.h->sem.h sequence so adding the sched.h into it will make all these .c depend on sched.h which is not that good. On the other hand the knowledge about the namespaces stuff is required in 4 .c files only.

Besides, this patch compiles out some auxiliary functions from ipc/sem.c, msg.c and shm.c files. It turned out that moving these functions into namespaces.c is not that easy because they use many other calls and macros from the original file. Moving them would make this patch complicated. On the other hand all these functions can be consolidated, so I will make it separately a bit later.

Signed-off-by: Pavel Emelyanov <xemul@openvz.org>

```
diff --git a/include/linux/ipc.h b/include/linux/ipc.h
index 96988d1..b882610 100644
--- a/include/linux/ipc.h
+++ b/include/linux/ipc.h
@@ -100,56 +100,6 @@ struct kern_ipc_perm
    void *security;
};

-struct ipc_ids;
-struct ipc_namespace {
-    struct kref kref;
-    struct ipc_ids *ids[3];
-
-    int sem_ctls[4];
-    int used_sems;
-
-    int msg_ctlmax;
```

```

- int msg_ctlmnb;
- int msg_ctlmni;
-
- size_t shm_ctlmax;
- size_t shm_ctlall;
- int shm_ctlmni;
- int shm_tot;
-};

-
-extern struct ipc_namespace init_ipc_ns;
-
-#ifdef CONFIG_SYSVIPC
#define INIT_IPC_NS(ns) .ns = &init_ipc_ns,
extern void free_ipc_ns(struct kref *kref);
extern struct ipc_namespace *copy_ipcs(unsigned long flags,
-    struct ipc_namespace *ns);
#else
#define INIT_IPC_NS(ns)
static inline struct ipc_namespace *copy_ipcs(unsigned long flags,
-    struct ipc_namespace *ns)
-{
- return ns;
-}
#endif
-
static inline struct ipc_namespace *get_ipc_ns(struct ipc_namespace *ns)
-{
#ifndef CONFIG_SYSVIPC
- if (ns)
- kref_get(&ns->kref);
#endif
- return ns;
-}

-
static inline void put_ipc_ns(struct ipc_namespace *ns)
-{
#ifndef CONFIG_SYSVIPC
- kref_put(&ns->kref, free_ipc_ns);
#endif
-}

#endif /* __KERNEL__ */

#endif /* _LINUX_IPC_H */
diff --git a/include/linux/ipc_namespace.h b/include/linux/ipc_namespace.h
new file mode 100644
index 0000000..6503532
--- /dev/null

```

```

+++ b/include/linux/ ipc_namespace.h
@@ -0,0 +1,67 @@
+#ifndef __IPC_NAMESPACE_H__
+#define __IPC_NAMESPACE_H__
+
+#include <linux/err.h>
+
+struct ipc_ids;
+struct ipc_namespace {
+    struct kref kref;
+    struct ipc_ids *ids[3];
+
+    int sem_ctls[4];
+    int used_sems;
+
+    int msg_ctlmax;
+    int msg_ctlmnb;
+    int msg_ctlmni;
+
+    size_t shm_ctlmax;
+    size_t shm_ctlall;
+    int shm_ctlmni;
+    int shm_tot;
+};
+
+extern struct ipc_namespace init_ipc_ns;
+
+#ifdef CONFIG_SYSVIPC
+#define INIT_IPC_NS(ns) .ns = &init_ipc_ns,
+#else
#define INIT_IPC_NS(ns)
#endif
+
+#if defined(CONFIG_SYSVIPC) && defined(CONFIG_IPC_NS)
+extern void free_ipc_ns(struct kref *kref);
+extern struct ipc_namespace *copy_ipcs(unsigned long flags,
+    struct ipc_namespace *ns);
+
+static inline struct ipc_namespace *get_ipc_ns(struct ipc_namespace *ns)
+{
+    if (ns)
+        kref_get(&ns->kref);
+    return ns;
+}
+
+static inline void put_ipc_ns(struct ipc_namespace *ns)
+{
+    kref_put(&ns->kref, free_ipc_ns);

```

```

+}
+#else
+static inline struct ipc_namespace *copy_ipcs(unsigned long flags,
+ struct ipc_namespace *ns)
+{
+ if (flags & CLONE_NEWIPC)
+ return ERR_PTR(-EINVAL);
+
+ return ns;
+}
+
+static inline struct ipc_namespace *get_ipc_ns(struct ipc_namespace *ns)
+{
+ return ns;
+}
+
+static inline void put_ipc_ns(struct ipc_namespace *ns)
+{
+}
+
#endif
#endif

diff --git a/init/Kconfig b/init/Kconfig
index d592aa2..b1aa7f1 100644
--- a/init/Kconfig
+++ b/init/Kconfig
@@ -416,6 +416,13 @@ config UTS_NS
    In this namespace tasks see different info provided with the
    uname() system call

+config IPC_NS
+ bool "IPC namespace"
+ depends on NAMESPACES && SYSVIPC
+ help
+   In this namespace tasks work with IPC ids which correspond to
+   different IPC objects in different namespaces
+
config BLK_DEV_INITRD
    bool "Initial RAM filesystem and RAM disk (initramfs/initrd) support"
    depends on BROKEN || !FRV
diff --git a/ipc/Makefile b/ipc/Makefile
index b93bba6..5fc5e33 100644
--- a/ipc/Makefile
+++ b/ipc/Makefile
@@ -7,4 +7,5 @@ obj-$(CONFIG_SYSVIPC) += util.o msgutil.o msg.o sem.o shm.o
obj-$(CONFIG_SYSVIPC_SYSCTL) += ipc_sysctl.o
obj_mq-$(CONFIG_COMPAT) += compat_mq.o
obj-$(CONFIG_POSIX_MQUEUE) += mqueue.o msgutil.o $(obj_mq-y)
+obj-$(CONFIG_IPC_NS) += namespace.o

```

```

diff --git a/ipc/ipc_sysctl.c b/ipc/ipc_sysctl.c
index 79e24e8..7f4235b 100644
--- a/ipc/ipc_sysctl.c
+++ b/ipc/ipc_sysctl.c
@@ -14,6 +14,7 @@
#include <linux/nsproxy.h>
#include <linux/sysctl.h>
#include <linux/uaccess.h>
+#include <linux/ ipc_namespace.h>

static void *get_ipc(ctl_table *table)
{
diff --git a/ipc/msg.c b/ipc/msg.c
index 4f1f263..03d0a47 100644
--- a/ipc/msg.c
+++ b/ipc/msg.c
@@ -36,6 +36,7 @@
#include <linux/seq_file.h>
#include <linux/rwsem.h>
#include <linux/nsproxy.h>
+#include <linux/ ipc_namespace.h>

#include <asm/current.h>
#include <asm/uaccess.h>
@@ -91,6 +92,7 @@ static void __msg_init_ns(struct ipc_namespace *ns, struct ipc_ids *ids)
 ipc_init_ids(ids);
}

+ifdef CONFIG_IPC_NS
int msg_init_ns(struct ipc_namespace *ns)
{
    struct ipc_ids *ids;
@@ -127,6 +129,7 @@ void msg_exit_ns(struct ipc_namespace *ns)
    kfree(ns->ids[IPC_MSG_IDS]);
    ns->ids[IPC_MSG_IDS] = NULL;
}
+endif

void __init msg_init(void)
{
diff --git a/ipc/namespace.c b/ipc/namespace.c
new file mode 100644
index 0000000..cef1139
--- /dev/null
+++ b/ipc/namespace.c
@@ -0,0 +1,73 @@
/*

```

```

+ * linux/ipc/namespace.c
+ * Copyright (C) 2006 Pavel Emelyanov <xemul@openvz.org> OpenVZ, SWsoft Inc.
+ */
+
+#
+#include <linux/ipc.h>
+#include <linux/msg.h>
+#include <linux/ipc_namespace.h>
+#include <linux/rcupdate.h>
+#include <linux/nsproxy.h>
+#include <linux/slab.h>
+
+#
+#include "util.h"
+
+static struct ipc_namespace *clone_ipc_ns(struct ipc_namespace *old_ns)
+{
+ int err;
+ struct ipc_namespace *ns;
+
+ err = -ENOMEM;
+ ns = kmalloc(sizeof(struct ipc_namespace), GFP_KERNEL);
+ if (ns == NULL)
+ goto err_mem;
+
+ err = sem_init_ns(ns);
+ if (err)
+ goto err_sem;
+ err = msg_init_ns(ns);
+ if (err)
+ goto err_msg;
+ err = shm_init_ns(ns);
+ if (err)
+ goto err_shm;
+
+ kref_init(&ns->kref);
+ return ns;
+
+err_shm:
+ msg_exit_ns(ns);
+err_msg:
+ sem_exit_ns(ns);
+err_sem:
+ kfree(ns);
+err_mem:
+ return ERR_PTR(err);
+}
+
+struct ipc_namespace *copy_ipcs(unsigned long flags, struct ipc_namespace *ns)
+{

```

```

+ struct ipc_namespace *new_ns;
+
+ BUG_ON(!ns);
+ get_ipc_ns(ns);
+
+ if (!(flags & CLONE_NEWIPC))
+ return ns;
+
+ new_ns = clone_ipc_ns(ns);
+
+ put_ipc_ns(ns);
+ return new_ns;
+}
+
+void free_ipc_ns(struct kref *kref)
+{
+ struct ipc_namespace *ns;
+
+ ns = container_of(kref, struct ipc_namespace, kref);
+ sem_exit_ns(ns);
+ msg_exit_ns(ns);
+ shm_exit_ns(ns);
+ kfree(ns);
+}
diff --git a/ipc/sem.c b/ipc/sem.c
index 40ab34d..19e0f6f 100644
--- a/ipc/sem.c
+++ b/ipc/sem.c
@@ -82,6 +82,7 @@
#include <linux/seq_file.h>
#include <linux/rwsem.h>
#include <linux/nsproxy.h>
+#include <linux/ipc_namespace.h>

#include <asm/uaccess.h>
#include "util.h"
@@ -128,6 +129,7 @@ static void __sem_init_ns(struct ipc_namespace *ns, struct ipc_ids *ids)
 ipc_init_ids(ids);
}

+#ifdef CONFIG_IPC_NS
int sem_init_ns(struct ipc_namespace *ns)
{
    struct ipc_ids *ids;
@@ -163,6 +165,7 @@ void sem_exit_ns(struct ipc_namespace *ns)
    kfree(ns->ids[IPC_SEM_IDS]);
    ns->ids[IPC_SEM_IDS] = NULL;
}

```

```

+#endif

void __init sem_init (void)
{
diff --git a/ipc/shm.c b/ipc/shm.c
index 05c97c7..4bbd04e 100644
--- a/ipc/shm.c
+++ b/ipc/shm.c
@@ -38,6 +38,7 @@
#include <linux/rwsem.h>
#include <linux/nsproxy.h>
#include <linux/mount.h>
+#include <linux/ipc_namespace.h>

#include <asm/uaccess.h>

@@ -96,6 +97,7 @@ static void do_shm_rmid(struct ipc_namespace *ns, struct shmid_kernel
*shp)
    shm_destroy(ns, shp);
}

+#ifdef CONFIG_IPC_NS
int shm_init_ns(struct ipc_namespace *ns)
{
    struct ipc_ids *ids;
@@ -131,6 +133,7 @@ void shm_exit_ns(struct ipc_namespace *ns)
    kfree(ns->ids[IPC_SHM_IDS]);
    ns->ids[IPC_SHM_IDS] = NULL;
}
#endif

void __init shm_init (void)
{
diff --git a/ipc/util.c b/ipc/util.c
index b42fb5..2574783 100644
--- a/ipc/util.c
+++ b/ipc/util.c
@@ -33,6 +33,7 @@
#include <linux/audit.h>
#include <linux/nsproxy.h>
#include <linux/rwsem.h>
+#include <linux/ipc_namespace.h>

#include <asm/unistd.h>

@@ -51,66 +52,6 @@ struct ipc_namespace init_ipc_ns = {
},
};

```

```

-static struct ipc_namespace *clone_ipc_ns(struct ipc_namespace *old_ns)
-{
- int err;
- struct ipc_namespace *ns;
-
- err = -ENOMEM;
- ns = kmalloc(sizeof(struct ipc_namespace), GFP_KERNEL);
- if (ns == NULL)
- goto err_mem;
-
- err = sem_init_ns(ns);
- if (err)
- goto err_sem;
- err = msg_init_ns(ns);
- if (err)
- goto err_msg;
- err = shm_init_ns(ns);
- if (err)
- goto err_shm;
-
- kref_init(&ns->kref);
- return ns;
-
-err_shm:
- msg_exit_ns(ns);
-err_msg:
- sem_exit_ns(ns);
-err_sem:
- kfree(ns);
-err_mem:
- return ERR_PTR(err);
-}
-
-struct ipc_namespace *copy_ipcs(unsigned long flags, struct ipc_namespace *ns)
-{
- struct ipc_namespace *new_ns;
-
- BUG_ON(!ns);
- get_ipc_ns(ns);
-
- if (!(flags & CLONE_NEWIPC))
- return ns;
-
- new_ns = clone_ipc_ns(ns);
-
- put_ipc_ns(ns);
- return new_ns;

```

```

-}

-
-void free_ipc_ns(struct kref *kref)
-{
- struct ipc_namespace *ns;
-
- ns = container_of(kref, struct ipc_namespace, kref);
- sem_exit_ns(ns);
- msg_exit_ns(ns);
- shm_exit_ns(ns);
- kfree(ns);
-}
-
/***
 * ipc_init - initialise IPC subsystem
 *
diff --git a/ipc/util.h b/ipc/util.h
index 9ffea40..fc6b729 100644
--- a/ipc/util.h
+++ b/ipc/util.h
@@ -20,6 +20,8 @@ void sem_init (void);
void msg_init (void);
void shm_init (void);

+struct ipc_namespace;
+
int sem_init_ns(struct ipc_namespace *ns);
int msg_init_ns(struct ipc_namespace *ns);
int shm_init_ns(struct ipc_namespace *ns);
diff --git a/kernel/nsproxy.c b/kernel/nsproxy.c
index 79f871b..f5d332c 100644
--- a/kernel/nsproxy.c
+++ b/kernel/nsproxy.c
@@ -21,6 +21,7 @@
#include <linux/utsname.h>
#include <linux/pid_namespace.h>
#include <net/net_namespace.h>
+#include <linux/ipc_namespace.h>

static struct kmem_cache *nsproxy_cachep;

--
```

1.5.3.4

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
