
Subject: [PATCH] memory cgroup enhancements take 4 [1/8] fix zone handling in
try_to_free_mem_cgroup_page

Posted by [KAMEZAWA Hiroyuki](#) on Wed, 31 Oct 2007 10:24:39 GMT

[View Forum Message](#) <> [Reply to Message](#)

Because NODE_DATA(node)->node_zonelist[] is guaranteed to contain all necessary zones, it is not necessary to use for_each_online_node.

And this for_each_online_node() makes reclaim routine start always from node 0. This is not good. This patch makes reclaim start from caller's node and just use usual (default) zonelist order.

Signed-off-by: KAMEZAWA Hiroyuki <kamezawa.hiroyu@jp.fujitsu.com>

mm/vmscan.c | 10 ++++-----
1 file changed, 4 insertions(+), 6 deletions(-)

Index: devel-2.6.23-mm1/mm/vmscan.c

```
=====
--- devel-2.6.23-mm1.orig/mm/vmscan.c
+++ devel-2.6.23-mm1/mm/vmscan.c
@@ -1375,15 +1375,13 @@ unsigned long try_to_free_mem_cgroup_pag
     .mem_cgroup = mem_cont,
     .isolate_pages = mem_cgroup_isolate_pages,
 };
- int node;
+ int node = numa_node_id();
   struct zone **zones;
   int target_zone = gfp_zone(GFP_HIGHUSER_MOVABLE);

- for_each_online_node(node) {
-   zones = NODE_DATA(node)->node_zonelist[target_zone].zones;
-   if (do_try_to_free_pages(zones, sc.gfp_mask, &sc))
-     return 1;
- }
+ zones = NODE_DATA(node)->node_zonelist[target_zone].zones;
+ if (do_try_to_free_pages(zones, sc.gfp_mask, &sc))
+   return 1;
+   return 0;
+ }
#endif
```

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
