
Subject: [PATCH][IPX] Use existing sock refcnt debugging infrastructure

Posted by [Pavel Emelianov](#) on Fri, 09 Nov 2007 13:42:05 GMT

[View Forum Message](#) <> [Reply to Message](#)

Just like in the af_packet.c, the ipx_sock_nr variable is used for debugging purposes.

Switch to using existing infrastructure. Thanks to Arnaldo for pointing this out.

Signed-off-by: Pavel Emelyanov <xemul@openvz.org>

```
diff --git a/net/ipx/af_ipx.c b/net/ipx/af_ipx.c
```

```
index a195a66..c76a952 100644
```

```
--- a/net/ipx/af_ipx.c
```

```
+++ b/net/ipx/af_ipx.c
```

```
@@ -92,11 +92,6 @@ extern int ipxrtr_route_skb(struct sk_buff *skb);
extern struct ipx_route *ipxrtr_lookup(__be32 net);
extern int ipxrtr_ioctl(unsigned int cmd, void __user *arg);
```

```
-#undef IPX_REFCNT_DEBUG
```

```
-#ifdef IPX_REFCNT_DEBUG
```

```
-atomic_t ipx_sock_nr;
```

```
-#endif
```

```
-
```

```
struct ipx_interface *ipx_interfaces_head(void)
```

```
{
    struct ipx_interface *rc = NULL;
```

```
@@ -151,14 +146,7 @@ static void ipx_destroy_socket(struct sock *sk)
```

```
{
    ipx_remove_socket(sk);
    skb_queue_purge(&sk->sk_receive_queue);
```

```
-#ifdef IPX_REFCNT_DEBUG
```

```
- atomic_dec(&ipx_sock_nr);
```

```
- printk(KERN_DEBUG "IPX socket %p released, %d are still alive\n", sk,
```

```
- atomic_read(&ipx_sock_nr));
```

```
- if (atomic_read(&sk->sk_refcnt) != 1)
```

```
- printk(KERN_DEBUG "Destruction sock ipx %p delayed, cnt=%d\n",
```

```
- sk, atomic_read(&sk->sk_refcnt));
```

```
-#endif
```

```
+ sk_refcnt_debug_dec(sk);
```

```
    sock_put(sk);
```

```
}
```

```
@@ -1384,11 +1372,8 @@ static int ipx_create(struct net *net, struct socket *sock, int protocol)
```

```
    sk = sk_alloc(net, PF_IPX, GFP_KERNEL, &ipx_proto);
```

```

if (!sk)
    goto out;
#ifdef IPX_REFCNT_DEBUG
- atomic_inc(&ipx_sock_nr);
- printk(KERN_DEBUG "IPX socket %p created, now we have %d alive\n", sk,
- atomic_read(&ipx_sock_nr));
#endif
+
+ sk_refcnt_debug_inc(sk);
  sock_init_data(sock, sk);
  sk->sk_no_check = 1; /* Checksum off by default */
  sock->ops = &ipx_dgram_ops;
@@ -1409,6 +1394,7 @@ static int ipx_release(struct socket *sock)

  sock_set_flag(sk, SOCK_DEAD);
  sock->sk = NULL;
+ sk_refcnt_debug_release(sk);
  ipx_destroy_socket(sk);
out:
  return 0;
--
1.5.3.4

```
