
Subject: [PATCH][IPV4] Remove bogus goto-s from ip_route_input_slow
Posted by [Pavel Emelianov](#) on Sat, 10 Nov 2007 14:27:50 GMT
[View Forum Message](#) <> [Reply to Message](#)

Both places look like

```
    if (err == XXX)
        goto yyy;
done:
```

while both yyy targets look like

```
    err = XXX;
    goto done;
```

so this is ok to remove the above if-s.

yyy labels are used in other places and are not removed.

Signed-off-by: Pavel Emelyanov <xemul@openvz.org>

diff --git a/net/ipv4/route.c b/net/ipv4/route.c

index 21b12de..c95b270 100644

--- a/net/ipv4/route.c

+++ b/net/ipv4/route.c

```
@ @ -1813,11 +1813,6 @ @ static int ip_route_input_slow(struct sk_buff *skb, __be32 daddr,
__be32 saddr,
    goto martian_destination;
```

```
    err = ip_mkroute_input(skb, &res, &fl, in_dev, daddr, saddr, tos);
- if (err == -ENOBUFS)
-     goto e_nobufs;
- if (err == -EINVAL)
-     goto e_inval;
-
```

```
done:
    in_dev_put(in_dev);
    if (free_res)
```

--

1.5.3.4
