

---

Subject: Re: [patch 1/1][NETNS][IPV6] protect addrconf from loopback registration  
Posted by [Daniel Lezcano](#) on Mon, 12 Nov 2007 17:01:22 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Eric W. Biederman wrote:

> "Denis V. Lunev" <den@sw.ru> writes:

>

>>> Index: linux-2.6-netns/net/ipv6/addrconf.c

>>> =====

>>> --- linux-2.6-netns.orig/net/ipv6/addrconf.c

>>> +++ linux-2.6-netns/net/ipv6/addrconf.c

>>> @@ -2272,7 +2272,8 @@ static int addrconf\_notify(struct notifi

>>>

>>> switch(event) {

>>> case NETDEV\_REGISTER:

>>> - if (!idev && dev->mtu >= IPV6\_MIN\_MTU) {

>>> + if (!(dev->flags & IFF\_LOOPBACK) &&

>>> + !idev && dev->mtu >= IPV6\_MIN\_MTU) {

>

> It is idev being true here for the loopback device that would

> prevent things not missing the REGISTER event.

>

> Hmm. But we do call ipv6\_add\_dev on loopback and now the loopback

> device is practically guaranteed to be the first device so we can

> probably just remove the special case in addrconf\_init.

>

> Anyway Daniels patch makes increasingly less sense the more I look

> at it.

Let me try to clarify:

\* when the init network namespace is created, the loopback is created first, before ipv6, and the notifier call chain for ipv6 is not setup, so the protocol does not receive the REGISTER event

\* when the init network namespace is destroyed during shutdown, the loopback is not unregistered, so there is no UNREGISTER event

\* when we create a new network namespace, a new instance of the loopback is created and a NETDEV\_REGISTER is sent to ipv6 because the notifier call chain has been setup by the init netns (while ipv6 protocol is not yet configured for the namespace which is being created)

\* when the network namespace exits, the loopback is unregistered after the ipv6 protocol but the NETDEV\_UNREGISTER is sent to addrconf\_notify while the ipv6 protocol has been destroyed.

The objective of the patch is to discard these events because they were never taken into account and they are not expected to be receive by ipv6 protocol.

---

Containers mailing list

Containers@lists.linux-foundation.org

<https://lists.linux-foundation.org/mailman/listinfo/containers>

---