Subject: Re: [patch -mm 2/4] mqueue namespace : add unshare support Posted by Oren Laadan on Thu, 29 Nov 2007 20:14:14 GMT

View Forum Message <> Reply to Message

Cedric Le Goater wrote: >>> Index: 2.6.24-rc3-mm2/include/linux/sched.h
>>> ==================================
>>> 2.6.24-rc3-mm2.orig/include/linux/sched.h >>> +++ 2.6.24-rc3-mm2/include/linux/sched.h
>>> @@ -27.6 +27.7 @@
>>> #define CLONE_NEWUSER 0x10000000 /* New user namespace */ >>> #define CLONE_NEWPID 0x20000000 /* New pid namespace */ >>> #define CLONE_NEWNET 0x40000000 /* New network namespace */ >>> +#define CLONE_NEWMQ 0x80000000 /* New posix mqueue namespace */ >>> That's it:) We've run out of clone flags on 32-bit platforms:(
>
> yes.
>
 I have been giving some thoughts to a clone2() to extend the flags but andrew is preparing to recycle CLONE_DETACHED and CLONE_STOPPED for 2.6.26. Some we might have some more time in front of us.

Two comments:

Oren.

- 1) Does it ever make any sense to clone the IPC namespace *without* doing so also for the MQ namespace or vice versa? Unless there is a good reason for doing so, a single CLONE_IPCMQ flag would suffice.
- 2) Before coming up with a new clone2() or other solution, what about the proposed (and debated) sys_indrect() -- if it gets merged it can provide the solution.