
Subject: [PATCH 06/10] sysfs: sysfs_chmod_file handle multiple superblocks
Posted by [ebiederm](#) on Sat, 01 Dec 2007 09:25:44 GMT
[View Forum Message](#) <> [Reply to Message](#)

Teach sysfs_chmod_file how to handle multiple sysfs superblocks.

Signed-off-by: Eric W. Biederman <ebiederm@xmission.com>

fs/sysfs/file.c | 51 ++++++-----
1 files changed, 28 insertions(+), 23 deletions(-)

diff --git a/fs/sysfs/file.c b/fs/sysfs/file.c

index 8c7bba0..ade6140 100644

--- a/fs/sysfs/file.c

+++ b/fs/sysfs/file.c

@@ -558,7 +558,8 @@ EXPORT_SYMBOL_GPL(sysfs_add_file_to_group);

int sysfs_chmod_file(struct kobject *kobj, struct attribute *attr, mode_t mode)

{
 struct sysfs_dirent *victim_sd = NULL;

- struct dentry *victim = NULL;

+ struct super_block *sb;

+ struct dentry *victim;

 struct inode * inode;

 struct iattr newattrs;

 int rc;

@@ -569,31 +570,35 @@ int sysfs_chmod_file(struct kobject *kobj, struct attribute *attr, mode_t mode)

 goto out;

 mutex_lock(&sysfs_rename_mutex);

- victim = sysfs_get_dentry(sysfs_sb, victim_sd);

- mutex_unlock(&sysfs_rename_mutex);

- if (IS_ERR(victim)) {

- rc = PTR_ERR(victim);

- victim = NULL;

- goto out;

- }

-

- inode = victim->d_inode;

-

- mutex_lock(&inode->i_mutex);

+ sysfs_grab_supers();

+ list_for_each_entry(sb, &sysfs_fs_type.fs_supers, s_instances) {

+ victim = sysfs_get_dentry(sb, victim_sd);

+ if (victim == ERR_PTR(-EXDEV))

+ continue;

+ if (IS_ERR(victim)) {

+ rc = PTR_ERR(victim);

```

+ victim = NULL;
+ goto out_unlock;
+ }

- newattrs.ia_mode = (mode & S_IALLUGO) | (inode->i_mode & ~S_IALLUGO);
- newattrs.ia_valid = ATTR_MODE | ATTR_CTIME;
- rc = notify_change(victim, &newattrs);
+ inode = victim->d_inode;
+ mutex_lock(&inode->i_mutex);
+ newattrs.ia_mode = (mode & S_IALLUGO) | (inode->i_mode & ~S_IALLUGO);
+ newattrs.ia_valid = ATTR_MODE | ATTR_CTIME;
+ rc = notify_change(victim, &newattrs);
+ if (rc == 0) {
+   mutex_lock(&sysfs_mutex);
+   victim_sd->s_mode = newattrs.ia_mode;
+   mutex_unlock(&sysfs_mutex);
+ }
+ mutex_unlock(&inode->i_mutex);

- if (rc == 0) {
-   mutex_lock(&sysfs_mutex);
-   victim_sd->s_mode = newattrs.ia_mode;
-   mutex_unlock(&sysfs_mutex);
+ dput(victim);
+ }
-
- mutex_unlock(&inode->i_mutex);
- out:
- dput(victim);
+out_unlock:
+ sysfs_release_supers();
+ mutex_unlock(&sysfs_rename_mutex);
+out:
+   sysfs_put(victim_sd);
+   return rc;
+ }
--
1.5.3.rc6.17.g1911

```

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
