
Subject: [PATCH 08/10] sysfs: Implement sysfs_delete_link and sysfs_rename_link
Posted by [ebiederm](#) on Sat, 01 Dec 2007 09:30:52 GMT

[View Forum Message](#) <> [Reply to Message](#)

When removing a symlink sysfs_remove_link does not provide enough information to figure out which tagged directory the symlink falls in. So I need sysfs_delete_link which is passed the target of the symlink to delete.

Further half the time when we are removing a symlink the code is actually renaming the symlink but not doing so explicitly because we don't have a symlink rename method. So I have added sysfs_rename_link as well.

Both of these functions now have enough information to find a symlink in a tagged directory. The only restriction is that they must be called before the target kobject is renamed or deleted. If they are called later I loose track of which tag the target kobject was marked with and can no longer find the old symlink to remove it.

Signed-off-by: Eric W. Biederman <ebiederm@xmission.com>

fs/sysfs/symlink.c | 31 ++++++

include/linux/sysfs.h | 17 ++++++

2 files changed, 48 insertions(+), 0 deletions(-)

diff --git a/fs/sysfs/symlink.c b/fs/sysfs/symlink.c

index b0f8070..89c98cb 100644

--- a/fs/sysfs/symlink.c

+++ b/fs/sysfs/symlink.c

@@ -80,6 +80,21 @@ int sysfs_create_link(struct kobject * kobj, struct kobject * target, const char

}

/**

+ * sysfs_delete_link - remove symlink in object's directory.

+ * @kobj: object we're acting for.

+ * @targ: object we're pointing to.

+ * @name: name of the symlink to remove.

+ *

+ * Unlike sysfs_remove_link sysfs_delete_link has enough information

+ * to successfully delete symlinks in tagged directories.

+ */

+void sysfs_delete_link(struct kobject *kobj, struct kobject *targ,

+ const char *name)

+{

+ sysfs_hash_and_remove(targ, kobj->sd, name);

+}

```

+
+/**
+ * sysfs_remove_link - remove symlink in object's directory.
+ * @kobj: object we're acting for.
+ * @name: name of the symlink to remove.
@@ -90,6 +105,22 @@ void sysfs_remove_link(struct kobject * kobj, const char * name)
+ sysfs_hash_and_remove(kobj, kobj->sd, name);
+
+
+/**
+ * sysfs_rename_link - rename symlink in object's directory.
+ * @kobj: object we're acting for.
+ * @targ: object we're pointing to.
+ * @old: previous name of the symlink.
+ * @new: new name of the symlink.
+ *
+ * A helper function for the common rename symlink idiom.
+ */
+int sysfs_rename_link(struct kobject *kobj, struct kobject *targ,
+ const char *old, const char *new)
+{
+ sysfs_delete_link(kobj, targ, old);
+ return sysfs_create_link(kobj, targ, new);
+}
+
+static int sysfs_get_target_path(struct sysfs_dirent *parent_sd,
+ struct sysfs_dirent *target_sd, char *path)
+{
diff --git a/include/linux/sysfs.h b/include/linux/sysfs.h
index c8d7a69..c2e8b0d 100644
--- a/include/linux/sysfs.h
+++ b/include/linux/sysfs.h
@@ -109,6 +109,12 @@ int __must_check sysfs_create_link(struct kobject *kobj, struct kobject
*target,
+ const char *name);
+void sysfs_remove_link(struct kobject *kobj, const char *name);
+
+int sysfs_rename_link(struct kobject *kobj, struct kobject *target,
+ const char *old_name, const char *new_name);
+
+void sysfs_delete_link(struct kobject *dir, struct kobject *targ,
+ const char *name);
+
+int __must_check sysfs_create_group(struct kobject *kobj,
+ const struct attribute_group *grp);
+void sysfs_remove_group(struct kobject *kobj,
@@ -195,6 +201,17 @@ static inline void sysfs_remove_link(struct kobject *kobj, const char
*name)

```

```

;
}

+static inline int sysfs_rename_link(struct kobject * k, struct kobject *t,
+    const char *old_name, const char * new_name)
+{
+ return 0;
+}
+
+static inline void sysfs_delete_link(struct kobject *k, struct kobject *t,
+    const char *name)
+{
+}
+
+static inline int sysfs_create_group(struct kobject *kobj,
+    const struct attribute_group *grp)
+{
+}
--
1.5.3.rc6.17.g1911

```

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
