
Subject: [PATCH net-2.6.25 2/2][IPV6] Use sysctl paths to register ipv6 sysctl tables
Posted by [Pavel Emelianov](#) on Mon, 03 Dec 2007 11:26:29 GMT

[View Forum Message](#) <> [Reply to Message](#)

This makes the ipv6.ko smaller and creates the ground needed
for net namespaces support in ipv6.ko ssctls.

Signed-off-by: Pavel Emelyanov <xemul@openvz.org>

```
diff --git a/net/ipv6/sysctl_net_ipv6.c b/net/ipv6/sysctl_net_ipv6.c
index 227efa7..0b5bec3 100644
--- a/net/ipv6/sysctl_net_ipv6.c
+++ b/net/ipv6/sysctl_net_ipv6.c
@@ -82,31 +82,17 @@ static ctl_table ipv6_table[] = {
 { .ctl_name = 0 }
};

-static struct ctl_table_header *ipv6_sysctl_header;
-
-static ctl_table ipv6_net_table[] = {
-{
-.ctl_name = NET_IPV6,
-.procname = "ipv6",
-.mode = 0555,
-.child = ipv6_table
-},
-{ .ctl_name = 0 }
+static struct ctl_path ipv6_ctl_path[] = {
+{ .procname = "net", .ctl_name = CTL_NET, },
+{ .procname = "ipv6", .ctl_name = NET_IPV6, },
+{ },
};

-static ctl_table ipv6_root_table[] = {
-{
-.ctl_name = CTL_NET,
-.procname = "net",
-.mode = 0555,
-.child = ipv6_net_table
-},
-{ .ctl_name = 0 }
-};
+static struct ctl_table_header *ipv6_sysctl_header;

void ipv6_sysctl_register(void)
{
```

```
- ipv6_sysctl_header = register_sysctl_table(ipv6_root_table);
+ ipv6_sysctl_header = register_sysctl_paths(ipv6_ctl_path, ipv6_table);
}
```

```
void ipv6_sysctl_unregister(void)
```

--
1.5.3.4
