
Subject: [PATCH net-2.6.25 1/2][INET] Merge sys.net.ipv4.ip_forward and sys.net.ipv4.conf.all.forwarding

Posted by [Pavel Emelianov](#) on Mon, 03 Dec 2007 14:29:37 GMT

[View Forum Message](#) <> [Reply to Message](#)

AFAIS these two entries should do the same thing - change the forwarding state on ipv4_devconf and on all the devices.

I propose to merge the handlers together using ctl paths.

The inet_forward_change() is static after this and I move it higher to make code organized like

<helpers (including this)>

<proc/sysctl handlers>

<tables>

rather than mixing it altogether.

Signed-off-by: Pavel Emelyanov <xemul@openvz.org>

diff --git a/include/linux/inetdevice.h b/include/linux/inetdevice.h

index d83fee2..dd093ea 100644

--- a/include/linux/inetdevice.h

+++ b/include/linux/inetdevice.h

@@ -135,7 +135,6 @@ extern struct in_device *inetdev_by_index(int);

extern __be32 inet_select_addr(const struct net_device *dev, __be32 dst, int scope);

extern __be32 inet_confirm_addr(const struct net_device *dev, __be32 dst, __be32 local, int scope);

extern struct in_ifaddr *inet_ifa_byprefix(struct in_device *in_dev, __be32 prefix, __be32 mask);

-extern void inet_forward_change(void);

static __inline__ int inet_ifa_match(__be32 addr, struct in_ifaddr *ifa)

{

diff --git a/net/ipv4/devinet.c b/net/ipv4/devinet.c

index c19c8db..0b5f042 100644

--- a/net/ipv4/devinet.c

+++ b/net/ipv4/devinet.c

@@ -1264,6 +1264,28 @@ static void devinet_copy_dflt_conf(int i)

read_unlock(&dev_base_lock);

}

+static void inet_forward_change(void)

+{

+ struct net_device *dev;

+ int on = IPV4_DEVCONF_ALL(FORWARDING);

+

+ IPV4_DEVCONF_ALL(ACCEPT_REDIRECTS) = !on;

```

+ IPV4_DEVCONF_DFLT(FORWARDING) = on;
+
+ read_lock(&dev_base_lock);
+ for_each_netdev(&init_net, dev) {
+ struct in_device *in_dev;
+ rcu_read_lock();
+ in_dev = __in_dev_get_rcu(dev);
+ if (in_dev)
+ IN_DEV_CONF_SET(in_dev, FORWARDING, on);
+ rcu_read_unlock();
+ }
+ read_unlock(&dev_base_lock);
+
+ rt_cache_flush(0);
+}
+
static int devinet_conf_proc(ctl_table *ctl, int write,
    struct file* filp, void __user *buffer,
    size_t *lenp, loff_t *ppos)
@@ -1333,28 +1355,6 @@ static int devinet_conf_sysctl(ctl_table *table, int __user *name, int
nlen,
    return 1;
}

```

```

-void inet_forward_change(void)
-{
- struct net_device *dev;
- int on = IPV4_DEVCONF_ALL(FORWARDING);
-
- IPV4_DEVCONF_ALL(ACCEPT_REDIRECTS) = !on;
- IPV4_DEVCONF_DFLT(FORWARDING) = on;
-
- read_lock(&dev_base_lock);
- for_each_netdev(&init_net, dev) {
- struct in_device *in_dev;
- rcu_read_lock();
- in_dev = __in_dev_get_rcu(dev);
- if (in_dev)
- IN_DEV_CONF_SET(in_dev, FORWARDING, on);
- rcu_read_unlock();
- }
- read_unlock(&dev_base_lock);
-
- rt_cache_flush(0);
-}
-
static int devinet_sysctl_forward(ctl_table *ctl, int write,
    struct file* filp, void __user *buffer,

```

```

    size_t *lenp, loff_t *ppos)
@@ -1537,6 +1537,27 @@ static void devinet_sysctl_unregister(struct ipv4_devconf *p)
}
#endif

+static struct ctl_table ctl_forward_entry[] = {
+ {
+ .ctl_name = NET_IPV4_FORWARD,
+ .procname = "ip_forward",
+ .data = &ipv4_devconf.data[
+   NET_IPV4_CONF_FORWARDING - 1],
+ .maxlen = sizeof(int),
+ .mode = 0644,
+ .proc_handler = devinet_sysctl_forward,
+ .strategy = devinet_conf_sysctl,
+ .extra1 = &ipv4_devconf,
+ },
+ { },
+};
+
+static __initdata struct ctl_path net_ipv4_path[] = {
+ { .procname = "net", .ctl_name = CTL_NET, },
+ { .procname = "ipv4", .ctl_name = NET_IPV4, },
+ { },
+};
+
void __init devinet_init(void)
{
    register_gifconf(PF_INET, inet_gifconf);
@@ -1550,6 +1571,7 @@ void __init devinet_init(void)
    &ipv4_devconf);
    __devinet_sysctl_register("default", NET_PROTO_CONF_DEFAULT,
    &ipv4_devconf_dflt);
+ register_sysctl_paths(net_ipv4_path, ctl_forward_entry);
#endif
}

diff --git a/net/ipv4/sysctl_net_ipv4.c b/net/ipv4/sysctl_net_ipv4.c
index bec6fe8..8c16077 100644
--- a/net/ipv4/sysctl_net_ipv4.c
+++ b/net/ipv4/sysctl_net_ipv4.c
@@ -35,62 +35,6 @@ struct ipv4_config ipv4_config;

#ifdef CONFIG_SYSCTL

-static
-int ipv4_sysctl_forward(ctl_table *ctl, int write, struct file * filp,
- void __user *buffer, size_t *lenp, loff_t *ppos)

```

```

- {
- int val = IPV4_DEVCONF_ALL(FORWARDING);
- int ret;
-
- ret = proc_dointvec(ctl, write, filp, buffer, lenp, ppos);
-
- if (write && IPV4_DEVCONF_ALL(FORWARDING) != val)
- inet_forward_change();
-
- return ret;
- }
-
- static int ipv4_sysctl_forward_strategy(ctl_table *table,
-     int __user *name, int nlen,
-     void __user *oldval, size_t __user *oldlenp,
-     void __user *newval, size_t newlen)
- {
- int *valp = table->data;
- int new;
-
- if (!newval || !newlen)
- return 0;
-
- if (newlen != sizeof(int))
- return -EINVAL;
-
- if (get_user(new, (int __user *)newval))
- return -EFAULT;
-
- if (new == *valp)
- return 0;
-
- if (oldval && oldlenp) {
- size_t len;
-
- if (get_user(len, oldlenp))
- return -EFAULT;
-
- if (len) {
- if (len > table->maxlen)
- len = table->maxlen;
- if (copy_to_user(oldval, valp, len))
- return -EFAULT;
- if (put_user(len, oldlenp))
- return -EFAULT;
- }
- }
- }
-

```

```

- *valp = new;
- inet_forward_change();
- return 1;
-}
-
extern seqlock_t sysctl_port_range_lock;
extern int sysctl_local_port_range[2];

@@ -290,15 +234,6 @@ ctl_table ipv4_table[] = {
    .proc_handler = &proc_dointvec
    },
    {
- .ctl_name = NET_IPV4_FORWARD,
- .procname = "ip_forward",
- .data = &IPV4_DEVCONF_ALL(FORWARDING),
- .maxlen = sizeof(int),
- .mode = 0644,
- .proc_handler = &ipv4_sysctl_forward,
- .strategy = &ipv4_sysctl_forward_strategy
- },
- {
    .ctl_name = NET_IPV4_DEFAULT_TTL,
    .procname = "ip_default_ttl",
    .data = &sysctl_ip_default_ttl,
--

```

1.5.3.4
