
Subject: [patch 05/38][IPV6] inet6_addr - make use of the new ipv6_chk_addr function

Posted by [Daniel Lezcano](#) on Mon, 03 Dec 2007 16:16:41 GMT

[View Forum Message](#) <> [Reply to Message](#)

The previous patch changed the ipv6_chk_addr API and tried to be focused on the network namespace check. A wrapper avoided to have the differents caller to be modified.

This patch removes the wrapper and propagate the function API change to all callers.

Signed-off-by: Daniel Lezcano <dlezcano@fr.ibm.com>

Signed-off-by: Benjamin Thery <benjamin.thery@bull.net>

include/net/addrconf.h | 9 +-----

net/ipv6/addrconf.c | 4 ++--

net/ipv6/af_inet6.c | 2 +-

net/ipv6/anycast.c | 2 +-

net/ipv6/datagram.c | 2 +-

net/ipv6/icmp.c | 2 +-

net/ipv6/ip6_tunnel.c | 8 ++++----

net/ipv6/ndisc.c | 2 +-

net/ipv6/raw.c | 2 +-

net/sctp/ipv6.c | 5 +++--

10 files changed, 16 insertions(+), 22 deletions(-)

Index: linux-2.6-netns/include/net/addrconf.h

=====

--- linux-2.6-netns.orig/include/net/addrconf.h

+++ linux-2.6-netns/include/net/addrconf.h

@@ -58,18 +58,11 @@ extern int addrconf_add_ifaddr(void __

extern int addrconf_del_ifaddr(void __user *arg);

extern int addrconf_set_dstaddr(void __user *arg);

-extern int __ipv6_chk_addr(struct net *net,

+extern int ipv6_chk_addr(struct net *net,

struct in6_addr *addr,

struct net_device *dev,

int strict);

-static inline int ipv6_chk_addr(struct in6_addr *addr,

- struct net_device *dev,

- int strict)

#{

- return __ipv6_chk_addr(&init_net, addr, dev, strict);

-}

-

```
#if defined(CONFIG_IPV6_MIP6) || defined(CONFIG_IPV6_MIP6_MODULE)
extern int  ipv6_chk_home_addr(struct in6_addr *addr);
#endif
```

Index: linux-2.6-netns/net/ipv6/addrconf.c

```
=====
```

```
--- linux-2.6-netns.orig/net/ipv6/addrconf.c
```

```
+++ linux-2.6-netns/net/ipv6/addrconf.c
```

```
@@ -1181,7 +1181,7 @@ static int ipv6_count_addresses(struct i
    return cnt;
}
```

```
-int __ipv6_chk_addr(struct net *net, struct in6_addr *addr,
+int ipv6_chk_addr(struct net *net, struct in6_addr *addr,
    struct net_device *dev, int strict)
```

```
{
    struct inet6_ifaddr * ifp;
@@ -1202,7 +1202,7 @@ int __ipv6_chk_addr(struct net *net, str
    return ifp != NULL;
}
```

```
-EXPORT_SYMBOL(__ipv6_chk_addr);
+EXPORT_SYMBOL(ipv6_chk_addr);
```

```
static
```

```
int ipv6_chk_same_addr(const struct in6_addr *addr, struct net_device *dev)
```

Index: linux-2.6-netns/net/ipv6/af_inet6.c

```
=====
```

```
--- linux-2.6-netns.orig/net/ipv6/af_inet6.c
```

```
+++ linux-2.6-netns/net/ipv6/af_inet6.c
```

```
@@ -314,7 +314,7 @@ int inet6_bind(struct socket *sock, stru
    */
```

```
    v4addr = LOOPBACK4_IPV6;
    if (!(addr_type & IPV6_ADDR_MULTICAST)) {
-   if (!ipv6_chk_addr(&addr->sin6_addr, dev, 0)) {
+   if (!ipv6_chk_addr(&init_net, &addr->sin6_addr, dev, 0)) {
        if (dev)
            dev_put(dev);
        err = -EADDRNOTAVAIL;
```

Index: linux-2.6-netns/net/ipv6/anycast.c

```
=====
```

```
--- linux-2.6-netns.orig/net/ipv6/anycast.c
```

```
+++ linux-2.6-netns/net/ipv6/anycast.c
```

```
@@ -89,7 +89,7 @@ int ipv6_sock_ac_join(struct sock *sk, i
    return -EPERM;
    if (ipv6_addr_is_multicast(addr))
        return -EINVAL;
-   if (ipv6_chk_addr(addr, NULL, 0))
+   if (ipv6_chk_addr(&init_net, addr, NULL, 0))
```

```
return -EINVAL;
```

```
pac = sock_kmalloc(sk, sizeof(struct ipv6_ac_socklist), GFP_KERNEL);
```

```
Index: linux-2.6-netns/net/ipv6/datagram.c
```

```
=====
```

```
--- linux-2.6-netns.orig/net/ipv6/datagram.c
```

```
+++ linux-2.6-netns/net/ipv6/datagram.c
```

```
@@ -550,7 +550,7 @@ int datagram_send_ctl(struct msghdr *msg
```

```
    return -ENODEV;
```

```
    }
```

```
    }
```

```
- if (!ipv6_chk_addr(&src_info->ipi6_addr, dev, 0)) {
```

```
+ if (!ipv6_chk_addr(&init_net, &src_info->ipi6_addr, dev, 0)) {
```

```
    if (dev)
```

```
        dev_put(dev);
```

```
    err = -EINVAL;
```

```
Index: linux-2.6-netns/net/ipv6/icmp.c
```

```
=====
```

```
--- linux-2.6-netns.orig/net/ipv6/icmp.c
```

```
+++ linux-2.6-netns/net/ipv6/icmp.c
```

```
@@ -331,7 +331,7 @@ void icmpv6_send(struct sk_buff *skb, in
```

```
    */
```

```
    addr_type = ipv6_addr_type(&hdr->daddr);
```

```
- if (ipv6_chk_addr(&hdr->daddr, skb->dev, 0))
```

```
+ if (ipv6_chk_addr(&init_net, &hdr->daddr, skb->dev, 0))
```

```
    saddr = &hdr->daddr;
```

```
/*
```

```
Index: linux-2.6-netns/net/ipv6/ip6_tunnel.c
```

```
=====
```

```
--- linux-2.6-netns.orig/net/ipv6/ip6_tunnel.c
```

```
+++ linux-2.6-netns/net/ipv6/ip6_tunnel.c
```

```
@@ -654,8 +654,8 @@ static inline int ip6_tnl_rcv_ctl(struct
```

```
    ldev = dev_get_by_index(&init_net, p->link);
```

```
    if ((ipv6_addr_is_multicast(&p->laddr) ||
```

```
-    likely(ipv6_chk_addr(&p->laddr, ldev, 0))) &&
```

```
-    likely(!ipv6_chk_addr(&p->raddr, NULL, 0)))
```

```
+    likely(ipv6_chk_addr(&init_net, &p->laddr, ldev, 0))) &&
```

```
+    likely(!ipv6_chk_addr(&init_net, &p->raddr, NULL, 0)))
```

```
    ret = 1;
```

```
    if (ldev)
```

```
@@ -789,12 +789,12 @@ static inline int ip6_tnl_xmit_ctl(struc
```

```
    if (p->link)
```

```
        ldev = dev_get_by_index(&init_net, p->link);
```

```

- if (unlikely(!ipv6_chk_addr(&p->laddr, ldev, 0)))
+ if (unlikely(!ipv6_chk_addr(&init_net, &p->laddr, ldev, 0)))
    printk(KERN_WARNING
           "%s xmit: Local address not yet configured!\n",
           p->name);
    else if (!ipv6_addr_is_multicast(&p->raddr) &&
-    unlikely(ipv6_chk_addr(&p->raddr, NULL, 0)))
+    unlikely(ipv6_chk_addr(&init_net, &p->raddr, NULL, 0)))
    printk(KERN_WARNING
           "%s xmit: Routing loop! "
           "Remote address found on this node!\n",

```

Index: linux-2.6-netns/net/ipv6/ndisc.c

```

=====
--- linux-2.6-netns.orig/net/ipv6/ndisc.c
+++ linux-2.6-netns/net/ipv6/ndisc.c
@@ -654,7 +654,7 @@ static void ndisc_solicit(struct neighbo
    struct in6_addr *target = (struct in6_addr *)&neigh->primary_key;
    int probes = atomic_read(&neigh->probes);

- if (skb && ipv6_chk_addr(&ipv6_hdr(skb)->saddr, dev, 1))
+ if (skb && ipv6_chk_addr(&init_net, &ipv6_hdr(skb)->saddr, dev, 1))
    saddr = &ipv6_hdr(skb)->saddr;

```

```

    if ((probes -= neigh->parms->ucast_probes) < 0) {

```

Index: linux-2.6-netns/net/ipv6/raw.c

```

=====
--- linux-2.6-netns.orig/net/ipv6/raw.c
+++ linux-2.6-netns/net/ipv6/raw.c
@@ -298,7 +298,7 @@ static int rawv6_bind(struct sock *sk, s
    v4addr = LOOPBACK4_IPV6;
    if (!(addr_type & IPV6_ADDR_MULTICAST)) {
        err = -EADDRNOTAVAIL;
-    if (!ipv6_chk_addr(&addr->sin6_addr, dev, 0)) {
+    if (!ipv6_chk_addr(&init_net, &addr->sin6_addr, dev, 0)) {
        if (dev)
            dev_put(dev);
        goto out;

```

Index: linux-2.6-netns/net/sctp/ipv6.c

```

=====
--- linux-2.6-netns.orig/net/sctp/ipv6.c
+++ linux-2.6-netns/net/sctp/ipv6.c
@@ -558,7 +558,7 @@ static int sctp_v6_available(union sctp_
    if (!(type & IPV6_ADDR_UNICAST))
        return 0;

- return ipv6_chk_addr(in6, NULL, 0);
+ return ipv6_chk_addr(&init_net, in6, NULL, 0);
}

```

```
/* This function checks if the address is a valid address to be used for
@@ -860,7 +860,8 @@ static int sctp_inet6_bind_verify(struct
    dev = dev_get_by_index(&init_net, addr->v6.sin6_scope_id);
    if (!dev)
        return 0;
-   if (!ipv6_chk_addr(&addr->v6.sin6_addr, dev, 0)) {
+   if (!ipv6_chk_addr(&init_net, &addr->v6.sin6_addr,
+       dev, 0)) {
        dev_put(dev);
        return 0;
    }
}
```

--

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
