
Subject: [patch 24/38][IPV6] rt6_stats - make rt6_stats per namespace

Posted by [Daniel Lezcano](#) on Mon, 03 Dec 2007 16:17:00 GMT

[View Forum Message](#) <> [Reply to Message](#)

The rt6_stats is now per namespace with this patch. It is allocated when a network namespace is created and freed when the network namespace exits and references are relative to the network namespace.

Signed-off-by: Benjamin Thery <benjamin.thery@bull.net>

Signed-off-by: Daniel Lezcano <dlezcano@fr.ibm.com>

net/ipv6/ip6_fib.c | 26 ++++++++-----

1 file changed, 15 insertions(+), 11 deletions(-)

Index: linux-2.6-netns/net/ipv6/ip6_fib.c

=====

--- linux-2.6-netns.orig/net/ipv6/ip6_fib.c

+++ linux-2.6-netns/net/ipv6/ip6_fib.c

@@ -601,6 +601,7 @@ static int fib6_add_rt2node(struct fib6_

{
 struct rt6_info *iter = NULL;

 struct rt6_info **ins;

+ struct net *net = &init_net;

 ins = &fn->leaf;

@@ -648,10 +649,10 @@ static int fib6_add_rt2node(struct fib6_

 rt->rt6i_node = fn;

 atomic_inc(&rt->rt6i_ref);

 inet6_rt_notify(RTM_NEWROUTE, rt, info);

- init_net.rt6_stats->fib_rt_entries++;

+ net->rt6_stats->fib_rt_entries++;

 if ((fn->fn_flags & RTN_RTINFO) == 0) {

- init_net.rt6_stats->fib_route_nodes++;

+ net->rt6_stats->fib_route_nodes++;

 fn->fn_flags |= RTN_RTINFO;

 }

@@ -1080,14 +1081,15 @@ static void fib6_del_route(struct fib6_n

{

 struct fib6_walker_t *w;

 struct rt6_info *rt = *rtp;

+ struct net *net = &init_net;

 RT6_TRACE("fib6_del_route\n");

```

/* Unlink it */
*rtp = rt->u.dst.rt6_next;
rt->rt6i_node = NULL;
- init_net.rt6_stats->fib_rt_entries--;
- init_net.rt6_stats->fib_discarded_routes++;
+ net->rt6_stats->fib_rt_entries--;
+ net->rt6_stats->fib_discarded_routes++;

/* Reset round-robin state, if necessary */
if (fn->rr_ptr == rt)
@@ -1113,7 +1115,7 @@ static void fib6_del_route(struct fib6_n
/* If it was last route, expunge its radix tree node */
if (fn->leaf == NULL) {
    fn->fn_flags &= ~RTN_RTINFO;
- init_net.rt6_stats->fib_route_nodes--;
+ net->rt6_stats->fib_route_nodes--;
    fn = fib6_repair_tree(fn);
}

@@ -1482,10 +1484,14 @@ static int fib6_net_init(struct net *net
    timer->base = &boot_tvec_bases;
    net->ip6_fib_timer = timer;

+ net->rt6_stats = kzalloc(sizeof(*net->rt6_stats), GFP_KERNEL);
+ if (!net->rt6_stats)
+ goto out_timer;
+
    net->fib_table_hash = kzalloc(sizeof(*net->fib_table_hash)*FIB_TABLE_HASHSZ,
        GFP_KERNEL);
    if (!net->fib_table_hash)
- goto out_timer;
+ goto out_rt6_stats;

    net->fib6_main_tbl = kzalloc(sizeof(*net->fib6_main_tbl), GFP_KERNEL);
    if (!net->fib6_main_tbl)
@@ -1512,6 +1518,8 @@ static int fib6_net_init(struct net *net

out_fib6_main_tbl:
    kfree(net->fib_table_hash);
+out_rt6_stats:
+    kfree(net->rt6_stats);
out_timer:
    kfree(timer);
out:
@@ -1528,6 +1536,7 @@ static void fib6_net_exit(struct net *ne
#endif
    kfree(net->fib6_main_tbl);
    kfree(net->fib_table_hash);

```

```

+ kfree(net->rt6_stats);
}

static struct pernet_operations fib6_net_ops = {
@@ -1542,10 +1551,6 @@ void __init fib6_init(void)
    0, SLAB_HWCACHE_ALIGN|SLAB_PANIC,
    NULL);

- init_net.rt6_stats = kzalloc(sizeof(*init_net.rt6_stats), GFP_KERNEL);
- if (!init_net.rt6_stats)
- panic("IPV6: failed to allocate rt6_stats.\n");
-
register_pernet_subsys(&fib6_net_ops);
__rtnl_register(PF_INET6, RTM_GETROUTE, NULL, inet6_dump_fib);
}
@@ -1553,6 +1558,5 @@ void __init fib6_init(void)
void fib6_gc_cleanup(void)
{
unregister_pernet_subsys(&fib6_net_ops);
- kfree(init_net.rt6_stats);
kmem_cache_destroy(fib6_node_kmem);
}

--

```

Containers mailing list

Containers@lists.linux-foundation.org

<https://lists.linux-foundation.org/mailman/listinfo/containers>
