
Subject: [PATCH] remove prototype of ip_rt_advice

Posted by [den](#) on Thu, 06 Dec 2007 10:17:02 GMT

[View Forum Message](#) <> [Reply to Message](#)

ip_rt_advice has been gone, so no need to keep prototype and debug message.

Signed-off-by: Denis V. Lunev <den@openvz.org>

```
--
diff --git a/include/net/route.h b/include/net/route.h
index f7ce625..59b0b19 100644
--- a/include/net/route.h
+++ b/include/net/route.h
@@ -109,7 +109,6 @@ struct in_device;
extern int ip_rt_init(void);
extern void ip_rt_redirect(__be32 old_gw, __be32 dst, __be32 new_gw,
                          __be32 src, struct net_device *dev);
-extern void ip_rt_advice(struct rtable **rp, int advice);
extern void rt_cache_flush(int how);
extern int __ip_route_output_key(struct rtable **, const struct flowi *flp);
extern int ip_route_output_key(struct rtable **, struct flowi *flp);
diff --git a/net/ipv4/route.c b/net/ipv4/route.c
index 134cab5..cefae61 100644
--- a/net/ipv4/route.c
+++ b/net/ipv4/route.c
@@ -1198,7 +1198,7 @@ static struct dst_entry *ipv4_negative_advice(struct dst_entry *dst)
    unsigned hash = rt_hash(rt->fl.fl4_dst, rt->fl.fl4_src,
                          rt->fl.oif);
    #if RT_CACHE_DEBUG >= 1
-   printk(KERN_DEBUG "ip_rt_advice: redirect to "
+   printk(KERN_DEBUG "ipv4_negative_advice: redirect to "
        "%u.%u.%u.%u/%02x dropped\n",
        NIPQUAD(rt->rt_dst), rt->fl.fl4_tos);
    #endif
```
