
Subject: [PATCH net-2.6.25 3/3]sysctl: make sysctl_somaxconn per-namespace
Posted by [Pavel Emelianov](#) on Fri, 07 Dec 2007 13:12:48 GMT
[View Forum Message](#) <> [Reply to Message](#)

Just move the variable on the struct net and adjust its usage.

Others sysctls from sys.net.core table are more difficult to virtualize (i.e. make them per-namespace), but I'll look at them as well a bit later.

Signed-off-by: Pavel Emelyanov <xemul@oenvz.org>

diff --git a/include/linux/socket.h b/include/linux/socket.h
index eb5bdd5..bd2b30a 100644

--- a/include/linux/socket.h

+++ b/include/linux/socket.h

```
@@ -24,7 +24,6 @@ struct __kernel_sockaddr_storage {  
#include <linux/types.h> /* pid_t */  
#include <linux/compiler.h> /* __user */
```

-extern int sysctl_somaxconn;

#ifdef CONFIG_PROC_FS

struct seq_file;

extern void socket_seq_show(struct seq_file *seq);

diff --git a/include/net/net_namespace.h b/include/net/net_namespace.h

index d593611..b62e31f 100644

--- a/include/net/net_namespace.h

+++ b/include/net/net_namespace.h

```
@@ -39,6 +39,7 @@ struct net {
```

```
/* core sysctls */
```

```
struct ctl_table_header *sysctl_core_hdr;
```

```
+ int sysctl_somaxconn;
```

```
/* List of all packet sockets. */
```

```
rwlock_t packet_sklist_lock;
```

diff --git a/net/core/sysctl_net_core.c b/net/core/sysctl_net_core.c

index dc4cf7d..130338f 100644

--- a/net/core/sysctl_net_core.c

+++ b/net/core/sysctl_net_core.c

```
@@ -127,7 +127,7 @@ static struct ctl_table net_core_table[] = {  
{
```

```
    .ctl_name = NET_CORE_SOMAXCONN,
```

```
    .procname = "somaxconn",
```

```
- .data = &sysctl_somaxconn,
```

```

+ .data = &init_net.sysctl_somaxconn,
  .maxlen = sizeof(int),
  .mode = 0644,
  .proc_handler = &proc_dointvec
@@ -161,6 +161,8 @@ static __net_init int sysctl_core_net_init(struct net *net)
{
    struct ctl_table *tbl, *tmp;

+ net->sysctl_somaxconn = SOMAXCONN;
+
    tbl = net_core_table;
    if (net != &init_net) {
        tbl = kmemdup(tbl, sizeof(net_core_table), GFP_KERNEL);
diff --git a/net/socket.c b/net/socket.c
index 9ebca5c..7651de0 100644
--- a/net/socket.c
+++ b/net/socket.c
@@ -1365,17 +1365,17 @@ asmlinkage long sys_bind(int fd, struct sockadr __user *umyaddr,
int addrlen)
    * ready for listening.
    */

-int sysctl_somaxconn __read_mostly = SOMAXCONN;
-
asmlinkage long sys_listen(int fd, int backlog)
{
    struct socket *sock;
    int err, fput_needed;
+ int somaxconn;

    sock = sockfd_lookup_light(fd, &err, &fput_needed);
    if (sock) {
- if ((unsigned)backlog > sysctl_somaxconn)
- backlog = sysctl_somaxconn;
+ somaxconn = sock->sk->sk_net->sysctl_somaxconn;
+ if ((unsigned)backlog > somaxconn)
+ backlog = somaxconn;

    err = security_socket_listen(sock, backlog);
    if (!err)
--
1.5.3.4

```
