
Subject: [PATCH] vlan: fix potential race in vlan_cleanup_module vs
vlan_ioctl_handler

Posted by [Pavel Emelianov](#) on Tue, 11 Dec 2007 10:25:11 GMT

[View Forum Message](#) <> [Reply to Message](#)

The vlan module cleanup function starts with

```
vlan_netlink_fini();  
vlan_ioctl_set(NULL);
```

The first call removes all the vlan devices and
the second one closes the vlan ioctl.

AFAIS there's a tiny race window between these two
calls - after rtnl unregistered all the vlans, but
the ioctl handler isn't set to NULL yet, user can
manage to call this ioctl and create one vlan device,
and that this function will later BUG_ON seeing
non-empty hashes.

I think, that we must first close the vlan ioctl
and only after this remove all the vlans with the
vlan_netlink_fini() call.

Signed-off-by: Pavel Emelyanov <xemul@openvz.org>

```
diff --git a/net/8021q/vlan.c b/net/8021q/vlan.c  
index 5b18315..4add9bd 100644  
--- a/net/8021q/vlan.c  
+++ b/net/8021q/vlan.c  
@@ -124,8 +124,8 @@ static void __exit vlan_cleanup_module(void)  
{  
    int i;  
  
-    vlan_netlink_fini();  
-    vlan_ioctl_set(NULL);  
+    vlan_netlink_fini();  
  
    /* Un-register us from receiving netdevice events */  
    unregister_netdevice_notifier(&vlan_notifier_block);
```
