

---

Subject: RE: init output

Posted by [Dietmar Maurer](#) on Tue, 11 Dec 2007 12:36:23 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

OK, tried it both ways, but output is truncated by vzctl stop.

For example the following init script:

```
-----  
#!/bin/sh  
  
# file must be there - create it  
echo >/var/log/init.log  
export CONSOLE=/var/log/init.log  
exec /sbin/init.org  
  
-----
```

then I start the VE and try to view the log:

```
> vzctl start 777
```

```
> tail -100f /var/lib/vz/root/777/var/log/init.log  
stty: standard input: Inappropriate ioctl for device  
/etc/rcS.d/S03udev: line 265: echo: write error: Operation not permitted  
Activating swap...done.  
mount: permission denied  
Cleaning up ifupdown....  
....
```

That works quite good so far, but when I stop the VE the file gets truncated:

```
tail: /var/lib/vz/root/777/var/log/init.log: file truncated
```

Any idea why? I already searched the sysvinit code sources, but found nothing there.

- Dietmar

```
> or you can replace /sbin/init with some script adding this to  
> env and running original init binary.
```

```
>
```

```
> Kirill
```

```
>
```

```
> Dietmar Maurer wrote:
```

> > But I cant do that with current vzctl, instead I need to modify the  
> > source?  
> >  
> > env.c 301: char \*envp[] = {"HOME=/", "TERM=linux",  
> > "CONSOLE=/var/log/init.log", NULL};  
> >

---