
Subject: [PATCH 1/9] sig: Fix mqueue pid
Posted by [ebiederm](#) on Wed, 12 Dec 2007 12:40:54 GMT
[View Forum Message](#) <> [Reply to Message](#)

Currently in the sig info for posix message queues we are reporting the task id and not the task group id. Given that this is a posix interface and that si_pid is defined by posix as returning the process id, we should be reporting the task group id.

So fix this interface.

Signed-off-by: Eric W. Biederman <ebiederm@xmission.com>

ipc/mqueue.c | 2 +-
1 files changed, 1 insertions(+), 1 deletions(-)

```
diff --git a/ipc/mqueue.c b/ipc/mqueue.c
index 7d1b8aa..d3feadf 100644
--- a/ipc/mqueue.c
+++ b/ipc/mqueue.c
@@ -510,7 +510,7 @@ static void __do_notify(struct mqueue_inode_info *info)
    sig_i.si_errno = 0;
    sig_i.si_code = SI_MESGQ;
    sig_i.si_value = info->notify.sigev_value;
-   sig_i.si_pid = task_pid_vnr(current);
+   sig_i.si_pid = task_tgid_vnr(current);
    sig_i.si_uid = current->uid;

    kill_pid_info(info->notify.sigev_signo,
```

--

1.5.3.rc6.17.g1911

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
