

---

Subject: [PATCH 5/9] pid: Update pid\_vnr to use task\_active\_pid\_ns  
Posted by [ebiederm](#) on Wed, 12 Dec 2007 12:48:18 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

There is no real additional cost in using task\_active\_pid\_ns and by doing so it means we do not need to audit the callers of pid\_vnr closely, to ensure they are always called on living processes.

Signed-off-by: Eric W. Biederman <[ebiederm@xmission.com](mailto:ebiederm@xmission.com)>

---

kernel/pid.c | 2 +-

1 files changed, 1 insertions(+), 1 deletions(-)

diff --git a/kernel/pid.c b/kernel/pid.c

index 54d7634..a7ecfce 100644

--- a/kernel/pid.c

+++ b/kernel/pid.c

@@ -444,7 +444,7 @@ pid\_t pid\_nr\_ns(struct pid \*pid, struct pid\_namespace \*ns)

pid\_t pid\_vnr(struct pid \*pid)

{

- return pid\_nr\_ns(pid, current->nsproxy->pid\_ns);

+ return pid\_nr\_ns(pid, task\_active\_pid\_ns(current));

}

EXPORT\_SYMBOL\_GPL(pid\_vnr);

--

1.5.3.rc6.17.g1911

---

Containers mailing list

[Containers@lists.linux-foundation.org](mailto:Containers@lists.linux-foundation.org)

<https://lists.linux-foundation.org/mailman/listinfo/containers>

---