
Subject: [PATCH 5/9] pid: Update pid_vnr to use task_active_pid_ns
Posted by [ebiederm](#) on Wed, 12 Dec 2007 12:48:18 GMT

[View Forum Message](#) <> [Reply to Message](#)

There is no real additional cost in using task_active_pid_ns and by doing so it means we do not need to audit the callers of pid_vnr closely, to ensure they are always called on living processes.

Signed-off-by: Eric W. Biederman <ebiederm@xmission.com>

kernel/pid.c | 2 +-
1 files changed, 1 insertions(+), 1 deletions(-)

diff --git a/kernel/pid.c b/kernel/pid.c

index 54d7634..a7ecfce 100644

--- a/kernel/pid.c

+++ b/kernel/pid.c

@@ -444,7 +444,7 @@ pid_t pid_nr_ns(struct pid *pid, struct pid_namespace *ns)

pid_t pid_vnr(struct pid *pid)

{
- return pid_nr_ns(pid, current->nsproxy->pid_ns);
+ return pid_nr_ns(pid, task_active_pid_ns(current));
}

EXPORT_SYMBOL_GPL(pid_vnr);

--

1.5.3.rc6.17.g1911

Containers mailing list

Containers@lists.linux-foundation.org

<https://lists.linux-foundation.org/mailman/listinfo/containers>
