
Subject: Re: Network configuration

Posted by [Yoann Moulin](#) on Wed, 12 Dec 2007 17:57:38 GMT

[View Forum Message](#) <> [Reply to Message](#)

> is it possible to know in the EXTERNAL_SCRIPT, for which interface, the
> script is execute ?

Well, I gave a look to the source code and got my answer (\$3)... it's working perfectly.

NETIF still the same :

```
NETIF="ifname=eth1.10,mac=00:16:3E:00:00:1E,host_ifname=veth10.10,host_mac=00:E0:81:4B:2F:DB;ifname=eth1.19,mac=00:16:3E:00:00:1E,host_ifname=veth10.19,host_mac=00:E0:81:4B:2F:DB"
```

and the script begin :

```
---- BEGIN SCRIPT ----
```

```
#!/bin/bash
```

```
# /usr/sbin/vznetaddroute
```

```
# a script to bring up virtual network interfaces (veth's) in a VE
```

```
CONFIGFILE=/etc/vz/conf/$VEID.conf
```

```
. $CONFIGFILE
```

```
VETH=$3
```

```
VZHOSTIF=`echo ${VETH} | cut -f1 -d"."`
```

```
VLAN=`echo ${VETH} | cut -f2 -d"."`
```

```
VETH_BRIDGE=brvlan${VLAN}
```

```
if [ ! -n "${VZHOSTIF}.${VLAN}" ]; then
```

```
    echo "According to $CONFIGFILE VE$VEID has no veth interface configured."
```

```
    exit 1
```

```
fi
```

```
if [ ! -n "${VETH_BRIDGE}" ]; then
```

```
    echo "According to $CONFIGFILE VE$VEID has no veth VETH_BRIDGE configured."
```

```
    exit 1
```

```
fi
```

```
echo "Adding interface ${VZHOSTIF}.${VLAN} to VETH_BRIDGE ${VETH_BRIDGE} on VE0"
```

```
if [ -z "`/usr/sbin/brctl show | /bin/grep ${VETH_BRIDGE}`" ]; then
```

```
    /usr/sbin/brctl addbr ${VETH_BRIDGE}
```

```
    /usr/sbin/brctl addif ${VETH_BRIDGE} eth1.${VLAN}
```

```
    /sbin/ip link set ${VETH_BRIDGE} up
```

```
fi
```

```
/usr/sbin/brctl addif ${VETH_BRIDGE} ${VZHOSTIF}.${VLAN}
```

```
/sbin/ip link set ${VZHOSTIF}.${VLAN} up
```

exit 0

---- END SCRIPT ----

sorry for the noise

Yoann
