

---

Subject: [PATCH net-2.6.25 19/19] [NETNS] Enable routing configuration in non-initial namespace.

Posted by [den](#) on Wed, 19 Dec 2007 15:24:49 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

I.e. remove the net != &init\_net checks from the places, that now can handle other-than-init net namespace.

Acked-by: Benjamin Thery <[benjamin.thery@bull.net](mailto:benjamin.thery@bull.net)>

Signed-off-by: Denis V. Lunev <[den@openvz.org](mailto:den@openvz.org)>

---

net/ipv4/fib\_frontend.c | 24 ++++-----

1 files changed, 4 insertions(+), 20 deletions(-)

diff --git a/net/ipv4/fib\_frontend.c b/net/ipv4/fib\_frontend.c

index a5c47fc..a5e2fb3 100644

--- a/net/ipv4/fib\_frontend.c

+++ b/net/ipv4/fib\_frontend.c

@@ -572,9 +572,6 @@ static int inet\_rtm\_delroute(struct sk\_buff \*skb, struct nlmsghdr\* nlh, void \*ar

struct fib\_table \*tb;  
int err;

- if (net != &init\_net)

- return -EINVAL;

-

err = rtm\_to\_fib\_config(net, skb, nlh, &cfg);

if (err < 0)

goto errout;

@@ -597,9 +594,6 @@ static int inet\_rtm\_newroute(struct sk\_buff \*skb, struct nlmsghdr\* nlh, void \*ar

struct fib\_table \*tb;  
int err;

- if (net != &init\_net)

- return -EINVAL;

-

err = rtm\_to\_fib\_config(net, skb, nlh, &cfg);

if (err < 0)

goto errout;

@@ -625,9 +619,6 @@ static int inet\_dump\_fib(struct sk\_buff \*skb, struct netlink\_callback \*cb) struct hlist\_head \*head;

int dumped = 0;

- if (net != &init\_net)

- return 0;

-

if (nlmsg\_len(cb->nlh) >= sizeof(struct rtmsg) &&

```

        ((struct rtmsg *) nlmsg_data(cb->nlh))->rtm_flags & RTM_F_CLONED)
    return ip_rt_dump(skb, cb);
@@ -931,9 +922,6 @@ static int fib_netdev_event(struct notifier_block *this, unsigned long
event, vo
    struct net_device *dev = ptr;
    struct in_device *in_dev = __in_dev_get_rtnl(dev);

- if (dev->nd_net != &init_net)
- return NOTIFY_DONE;
-
    if (event == NETDEV_UNREGISTER) {
        fib_disable_ip(dev, 2);
        return NOTIFY_DONE;
@@ -1013,10 +1001,6 @@ static int __net_init fib_net_init(struct net *net)
{
    int error;

- error = 0;
- if (net != &init_net)
- goto out;
-
    error = ip_fib_net_init(net);
    if (error < 0)
        goto out;
--

```

1.5.3.rc5

---