
Subject: [PATCH net-2.6.25 2/6][NETNS]: Make the __addrconf_sysctl_register return an error

Posted by [Pavel Emelianov](#) on Thu, 10 Jan 2008 14:01:13 GMT

[View Forum Message](#) <> [Reply to Message](#)

This error code will be needed to abort the namespace creation if needed.

Probably, this is to be checked when a new device is created (currently it is ignored).

Signed-off-by: Pavel Emelyanov <xemul@openvz.org>

net/ipv6/addrconf.c | 6 +++---

1 files changed, 3 insertions(+), 3 deletions(-)

diff --git a/net/ipv6/addrconf.c b/net/ipv6/addrconf.c

index 27b35dd..18d4334 100644

--- a/net/ipv6/addrconf.c

+++ b/net/ipv6/addrconf.c

@@ -4044,7 +4044,7 @@ static struct addrconf_sysctl_table

},

};

-static void __addrconf_sysctl_register(char *dev_name, int ctl_name,

+static int __addrconf_sysctl_register(char *dev_name, int ctl_name,

struct inet6_dev *idev, struct ipv6_devconf *p)

{

int i;

@@ -4088,14 +4088,14 @@ static void __addrconf_sysctl_register(char *dev_name, int
ctl_name,

goto free_procname;

p->sysctl = t;

- return;

+ return 0;

free_procname:

kfree(t->dev_name);

free:

kfree(t);

out:

- return;

+ return -ENOBUFFS;

}

static void __addrconf_sysctl_unregister(struct ipv6_devconf *p)

--

1.5.3.4
