
Subject: Centos 5.0 problem with new kernel, nfs in VE not working.

Posted by [JimL](#) on Sat, 19 Jan 2008 17:12:47 GMT

[View Forum Message](#) <> [Reply to Message](#)

NFS has stopped working in a VE running under Centos 5.0.

See the following:

HN VE0 Centos.

```
[root@server1 ~]# uname -r
2.6.18-53.1.4.el5.028stab053.4
```

be sure the file systems are exported

```
root@walnut:~# ssh 192.168.2.90
root@192.168.2.90's password:
```

```
root@blackie:~# exportfs
/data1/mail/www
    192.168.2.50
/data1/mail/www
    192.168.2.44
/data1/mail/db 192.168.2.50
/data1/mail/db 192.168.2.44
root@blackie:~# exit
```

try to mount one from a VE

```
root@walnut:~# mount /var/lib/omega/data/
mount to NFS server '192.168.2.90' failed: server is down.
```

no it isn't

```
root@walnut:~# ping 192.168.2.90
PING 192.168.2.90 (192.168.2.90) 56(84) bytes of data.
64 bytes from 192.168.2.90: icmp_seq=1 ttl=63 time=313 ms
64 bytes from 192.168.2.90: icmp_seq=2 ttl=63 time=0.183 ms
```

--- 192.168.2.90 ping statistics ---

2 packets transmitted, 2 received, 0% packet loss, time 1000ms
rtt min/avg/max/mdev = 0.183/156.837/313.491/156.654 ms

prove we are .50

```
root@walnut:~# ifconfig
```

```
...
venet0:0 Link encap:UNSPEC HWaddr 00-00-00-00-00-00-00-00-00-00-00-00-00-00-00-00
    inet addr:192.168.2.50 P-t-P:192.168.2.50 Bcast:0.0.0.0 Mask:255.255.255.255
    UP BROADCAST POINTOPOINT RUNNING NOARP MTU:1500 Metric:1
```

Try from another system, not a VE

```
root@chinaberry:~# mount /var/lib/omega/data/
root@chinaberry:~# ifconfig
eth2    Link encap:Ethernet  HWaddr 00:16:E6:36:35:0A
        inet addr:192.168.2.44  Bcast:192.168.2.255  Mask:255.255.255.0
        inet6 addr: fe80::216:e6ff:fe36:350a/64 Scope:Link
        UP BROADCAST RUNNING MULTICAST  MTU:1500  Metric:1
        RX packets:10267 errors:0 dropped:0 overruns:0 frame:0
        TX packets:10315 errors:0 dropped:0 overruns:0 carrier:0
        collisions:0 txqueuelen:1000
        RX bytes:4847869 (4.6 MiB)  TX bytes:1017159 (993.3 KiB)
        Interrupt:17 Base address:0xc000
root@chinaberry:~# mount| grep nfs
192.168.2.90:/data1/mail/db on /var/lib/omega/data type nfs
(rw,rsize=8192,wsiz=8192,timeo=14,intr,addr=192.168.2.90)
```

It worked on that system, now look to see if nfs is on

```
[root@server1 conf]# grep -i nfs 1002.conf
FEATURES="nfs:on "
[root@server1 conf]# grep IP 1002.conf
NUMIPTENT="128:128"
IP_ADDRESS="192.168.2.50"
[root@server1 conf]#
### so nfs is on and the ip is right.
```

I did notice this in the /proc/userbeancounters which bothers me a bit.

numothersock	17	20	80	80	29
--------------	----	----	----	----	----

How can I have exceeded 80 sockets when the max is 20?

Thanks,
Jim.
