
Subject: [PATCH 6/6 net-2.6.25] [NETNS] Pass correct namespace in ip_rt_get_source.

Posted by [den](#) on Mon, 21 Jan 2008 14:50:46 GMT

[View Forum Message](#) <> [Reply to Message](#)

ip_rt_get_source is the infamous place for which dst_ifdown kludges have been implemented. This means that rt->u.dst.dev can be safely dereferenced obtain nd_net.

Signed-off-by: Denis V. Lunev <den@openvz.org>

net/ipv4/route.c | 2 +-
1 files changed, 1 insertions(+), 1 deletions(-)

diff --git a/net/ipv4/route.c b/net/ipv4/route.c

index b3c6122..ede0571 100644

--- a/net/ipv4/route.c

+++ b/net/ipv4/route.c

@@ -1559,7 +1559,7 @@ void ip_rt_get_source(u8 *addr, struct rtable *rt)

```
    if (rt->fl.iif == 0)
        src = rt->rt_src;
- else if (fib_lookup(&init_net, &rt->fl, &res) == 0) {
+ else if (fib_lookup(rt->u.dst.dev->nd_net, &rt->fl, &res) == 0) {
    src = FIB_RES_PREFSRC(res);
    fib_res_put(&res);
} else
```

--

1.5.3.rc5
