

---

Subject: Re: Is NFS virtualized fully?

Posted by [dev](#) on Thu, 13 Apr 2006 06:15:57 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Suggested by Babyface on IRC:

<Babyface> mount --bind /path /to/path

<Babyface> for example

<dowdle> That command is within the VPS?

<Babyface> mount --bind /nfsroot /vz/root/<vpsid>/mnt

<Babyface> no on hostnode

<dowdle> Ok, cool. Thanks I'll try that now.

<Babyface> and vps must be started before

<Babyface> or mounted

<Babyface> so better to create some kind of /etc/sysconfig/vz-scripts/<vpsid>.mount and .umount files

<Babyface> then on vps startup it is automatically mounted

<dowdle> Wow... that worked like instantly! Thanks very much.

<dowdle> Ok, sure... about the mount and unmount scripts... as I want that to be automatic. So, if I create scripts with those names, they will be automatically parsed upon VPS startup?

<Babyface> yes

<dowdle> Right on.

<dowdle> Thanks Babyface!

<-- ckoehn has quit ("7:42pm| (@DenisGe) ich schneid nie wieder samstags nachts 2 uhr haare alleine")

<Babyface> mount file should look like

<Babyface> #!/bin/bash

<Babyface> # if one of these files does not exist then something is really broken

<Babyface> [ -f "\${VE\_CONFFILE}" ] || exit 1

<Babyface> # mount nfsroot.

<Babyface> mount --bind /nfsroot /vz/root/<vpsid>/mnt

<Babyface> exit \${?}

<Babyface> and must be executable

<Babyface> umount like

<Babyface> #!/bin/bash

<Babyface> # if one of these files does not exist then something is really broken

<Babyface> [ -f "\${VE\_CONFFILE}" ] || exit 1

<Babyface> # umount nfsroot.

<Babyface> umount /vz/root/<vpsid>/mnt

<Babyface> exit \${?}

<Babyface> also executable

---