
Subject: [PATCH 5/7 net-2.6.25] [IPV4]: fib_sync_down rework.

Posted by [den](#) on Fri, 25 Jan 2008 13:52:01 GMT

[View Forum Message](#) <> [Reply to Message](#)

fib_sync_down can be called with an address and with a device. In reality it is called either with address OR with a device. The codepath inside is completely different, so lets separate it into two calls for these two cases.

Signed-off-by: Denis V. Lunev <den@openvz.org>

```
include/net/ip_fib.h      | 3 +-
net/ipv4/fib_frontend.c   | 4 +-
net/ipv4/fib_semantics.c  | 104 ++++++-----
3 files changed, 57 insertions(+), 54 deletions(-)
```

diff --git a/include/net/ip_fib.h b/include/net/ip_fib.h

index 9daa60b..1b2f008 100644

--- a/include/net/ip_fib.h

+++ b/include/net/ip_fib.h

@@ -218,7 +218,8 @@ extern void fib_select_default(struct net *net, const struct flowi *flp,

/* Exported by fib_semantics.c */

extern int ip_fib_check_default(__be32 gw, struct net_device *dev);

-extern int fib_sync_down(__be32 local, struct net_device *dev, int force);

+extern int fib_sync_down_dev(struct net_device *dev, int force);

+extern int fib_sync_down_addr(__be32 local);

extern int fib_sync_up(struct net_device *dev);

extern __be32 __fib_res_prefsrc(struct fib_result *res);

extern void fib_select_multipath(const struct flowi *flp, struct fib_result *res);

diff --git a/net/ipv4/fib_frontend.c b/net/ipv4/fib_frontend.c

index d0507f4..d69ffa2 100644

--- a/net/ipv4/fib_frontend.c

+++ b/net/ipv4/fib_frontend.c

@@ -808,7 +808,7 @@ static void fib_del_ifaddr(struct in_ifaddr *ifa)

First of all, we scan fib_info list searching

for stray nexthop entries, then ignite fib_flush.

*/

- if (fib_sync_down(ifa->ifa_local, NULL, 0))

+ if (fib_sync_down_addr(ifa->ifa_local))

fib_flush(dev->nd_net);

}

}

@@ -898,7 +898,7 @@ static void nl_fib_lookup_exit(struct net *net)

static void fib_disable_ip(struct net_device *dev, int force)

{

- if (fib_sync_down(0, dev, force))

```

+ if (fib_sync_down_dev(dev, force))
    fib_flush(dev->nd_net);
    rt_cache_flush(0);
    arp_ifdown(dev);
diff --git a/net/ipv4/fib_semantics.c b/net/ipv4/fib_semantics.c
index c791286..5beff2e 100644
--- a/net/ipv4/fib_semantics.c
+++ b/net/ipv4/fib_semantics.c
@@ -1031,70 +1031,72 @@ nla_put_failure:
    referring to it.
    - device went down -> we must shutdown all nexthops going via it.
    */
-
-
-int fib_sync_down(__be32 local, struct net_device *dev, int force)
+int fib_sync_down_addr(__be32 local)
{
    int ret = 0;
- int scope = RT_SCOPE_NOWHERE;
-
- if (force)
-     scope = -1;
+ unsigned int hash = fib_laddr_hashfn(local);
+ struct hlist_head *head = &fib_info_laddrhash[hash];
+ struct hlist_node *node;
+ struct fib_info *fi;

- if (local && fib_info_laddrhash) {
-     unsigned int hash = fib_laddr_hashfn(local);
-     struct hlist_head *head = &fib_info_laddrhash[hash];
-     struct hlist_node *node;
-     struct fib_info *fi;
+ if (fib_info_laddrhash == NULL || local == 0)
+     return 0;

- hlist_for_each_entry(fi, node, head, fib_lhash) {
-     if (fi->fib_prefsrc == local) {
-         fi->fib_flags |= RTNH_F_DEAD;
-         ret++;
-     }
+ hlist_for_each_entry(fi, node, head, fib_lhash) {
+     if (fi->fib_prefsrc == local) {
+         fi->fib_flags |= RTNH_F_DEAD;
+         ret++;
+     }
+ }
+ return ret;
+}

```

```

- if (dev) {
- struct fib_info *prev_fi = NULL;
- unsigned int hash = fib_devindex_hashfn(dev->ifindex);
- struct hlist_head *head = &fib_info_devhash[hash];
- struct hlist_node *node;
- struct fib_nh *nh;
+int fib_sync_down_dev(struct net_device *dev, int force)
+{
+ int ret = 0;
+ int scope = RT_SCOPE_NOWHERE;
+ struct fib_info *prev_fi = NULL;
+ unsigned int hash = fib_devindex_hashfn(dev->ifindex);
+ struct hlist_head *head = &fib_info_devhash[hash];
+ struct hlist_node *node;
+ struct fib_nh *nh;

- hlist_for_each_entry(nh, node, head, nh_hash) {
- struct fib_info *fi = nh->nh_parent;
- int dead;
+ if (force)
+ scope = -1;

- BUG_ON(!fi->fib_nhs);
- if (nh->nh_dev != dev || fi == prev_fi)
- continue;
- prev_fi = fi;
- dead = 0;
- change_nexthops(fi) {
- if (nh->nh_flags&RTNH_F_DEAD)
- dead++;
- else if (nh->nh_dev == dev &&
- nh->nh_scope != scope) {
- nh->nh_flags |= RTNH_F_DEAD;
+ hlist_for_each_entry(nh, node, head, nh_hash) {
+ struct fib_info *fi = nh->nh_parent;
+ int dead;
+
+ BUG_ON(!fi->fib_nhs);
+ if (nh->nh_dev != dev || fi == prev_fi)
+ continue;
+ prev_fi = fi;
+ dead = 0;
+ change_nexthops(fi) {
+ if (nh->nh_flags&RTNH_F_DEAD)
+ dead++;
+ else if (nh->nh_dev == dev &&
+ nh->nh_scope != scope) {
+ nh->nh_flags |= RTNH_F_DEAD;

```

```

#ifdef CONFIG_IP_ROUTE_MULTIPATH
-   spin_lock_bh(&fib_multipath_lock);
-   fi->fib_power -= nh->nh_power;
-   nh->nh_power = 0;
-   spin_unlock_bh(&fib_multipath_lock);
+   spin_lock_bh(&fib_multipath_lock);
+   fi->fib_power -= nh->nh_power;
+   nh->nh_power = 0;
+   spin_unlock_bh(&fib_multipath_lock);
#endif
-   dead++;
-   }
+   dead++;
+   }
#ifdef CONFIG_IP_ROUTE_MULTIPATH
-   if (force > 1 && nh->nh_dev == dev) {
-       dead = fi->fib_nhs;
-       break;
-   }
-#endif
-   } endfor_nexthops(fi)
-   if (dead == fi->fib_nhs) {
-       fi->fib_flags |= RTNH_F_DEAD;
-       ret++;
+   if (force > 1 && nh->nh_dev == dev) {
+       dead = fi->fib_nhs;
+       break;
+   }
+#endif
+   } endfor_nexthops(fi)
+   if (dead == fi->fib_nhs) {
+       fi->fib_flags |= RTNH_F_DEAD;
+       ret++;
+   }
+   }

--
1.5.3.rc5

```
