
Subject: [PATCH 2/3] netns netfilter: netns propagation for
/proc/net/*_tables_names

Posted by [Alexey Dobriyan](#) on Fri, 25 Jan 2008 16:44:29 GMT

[View Forum Message](#) <> [Reply to Message](#)

Propagate netns together with AF down to ->start/->next/->stop
iterators. Choose table based on netns and AF for showing.

Signed-off-by: Alexey Dobriyan <adobriyan@sw.ru>

net/netfilter/x_tables.c | 31 ++++++-----
1 file changed, 19 insertions(+), 12 deletions(-)

--- a/net/netfilter/x_tables.c

+++ b/net/netfilter/x_tables.c

@@ -726,27 +726,33 @@ void *xt_unregister_table(struct xt_table *table)
EXPORT_SYMBOL_GPL(xt_unregister_table);

#ifdef CONFIG_PROC_FS

+struct xt_names_priv {

+ struct seq_net_private p;

+ int af;

+};

static void *xt_table_seq_start(struct seq_file *seq, loff_t *pos)
{

- struct proc_dir_entry *pde = (struct proc_dir_entry *)seq->private;

- u_int16_t af = (unsigned long)pde->data;

+ struct xt_names_priv *priv = seq->private;

+ struct net *net = priv->p.net;

+ int af = priv->af;

mutex_lock(&xt[af].mutex);

- return seq_list_start(&init_net.xt.tables[af], *pos);

+ return seq_list_start(&net->xt.tables[af], *pos);

}

static void *xt_table_seq_next(struct seq_file *seq, void *v, loff_t *pos)
{

- struct proc_dir_entry *pde = (struct proc_dir_entry *)seq->private;

- u_int16_t af = (unsigned long)pde->data;

+ struct xt_names_priv *priv = seq->private;

+ struct net *net = priv->p.net;

+ int af = priv->af;

- return seq_list_next(v, &init_net.xt.tables[af], pos);

+ return seq_list_next(v, &net->xt.tables[af], pos);

}

```

static void xt_table_seq_stop(struct seq_file *seq, void *v)
{
- struct proc_dir_entry *pde = seq->private;
- u_int16_t af = (unsigned long)pde->data;
+ struct xt_names_priv *priv = seq->private;
+ int af = priv->af;

    mutex_unlock(&xt[af].mutex);
}
@@ -771,12 +777,13 @@ static const struct seq_operations xt_table_seq_ops = {
static int xt_table_open(struct inode *inode, struct file *file)
{
    int ret;
+ struct xt_names_priv *priv;

- ret = seq_open(file, &xt_table_seq_ops);
+ ret = seq_open_net(inode, file, &xt_table_seq_ops,
+     sizeof(struct xt_names_priv));
    if (!ret) {
- struct seq_file *seq = file->private_data;
-
- seq->private = PDE(inode);
+ priv = ((struct seq_file *)file->private_data)->private;
+ priv->af = (unsigned long)PDE(inode)->data;
    }
    return ret;
}

```
