
Subject: [PATCH 2.6.24-rc8-mm1 05/15] IPC/semaphores: remove one unused parameter from semctl_down()

Posted by [Pierre Peiffer](#) on Tue, 29 Jan 2008 16:02:34 GMT

[View Forum Message](#) <> [Reply to Message](#)

From: Pierre Peiffer <pierre.peiffer@bull.net>

semctl_down() takes one unused parameter: semnum.

This patch proposes to get rid of it.

Signed-off-by: Pierre Peiffer <pierre.peiffer@bull.net>

Acked-by: Serge Hallyn <serue@us.ibm.com>

ipc/sem.c | 6 +++---

1 file changed, 3 insertions(+), 3 deletions(-)

Index: b/ipc/sem.c

=====

--- a/ipc/sem.c

+++ b/ipc/sem.c

@@ -882,8 +882,8 @@ static inline unsigned long copy_sem_id_f

* to be held in write mode.

* NOTE: no locks must be held, the rw_mutex is taken inside this function.

*/

-static int semctl_down(struct ipc_namespace *ns, int semid, int semnum,
- int cmd, int version, union semun arg)

+static int semctl_down(struct ipc_namespace *ns, int semid,
+ int cmd, int version, union semun arg)

{

struct sem_array *sma;

int err;

@@ -974,7 +974,7 @@ asmlinkage long sys_semctl (int semid, i
return err;

case IPC_RMID:

case IPC_SET:

- err = semctl_down(ns, semid, semnum, cmd, version, arg);

+ err = semctl_down(ns, semid, cmd, version, arg);

return err;

default:

return -EINVAL;

--

Pierre Peiffer

Containers mailing list

Containers@lists.linux-foundation.org

<https://lists.linux-foundation.org/mailman/listinfo/containers>
