

---

Subject: [PATCH 2.6.24-rc8-mm1 05/15] IPC/semaphores: remove one unused parameter from semctl\_down()

Posted by [Pierre Peiffer](#) on Tue, 29 Jan 2008 16:02:34 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

From: Pierre Peiffer <pierre.peiffer@bull.net>

semctl\_down() takes one unused parameter: semnum.  
This patch proposes to get rid of it.

Signed-off-by: Pierre Peiffer <pierre.peiffer@bull.net>

Acked-by: Serge Hallyn <serue@us.ibm.com>

---

ipc/sem.c | 6 +----  
1 file changed, 3 insertions(+), 3 deletions(-)

Index: b/ipc/sem.c

---

```
--- a/ipc/sem.c
+++ b/ipc/sem.c
@@ -882,8 +882,8 @@ static inline unsigned long copy_semid_f
 * to be held in write mode.
 * NOTE: no locks must be held, the rw_mutex is taken inside this function.
 */
-static int semctl_down(struct ipc_namespace *ns, int semid, int semnum,
- int cmd, int version, union semun arg)
+static int semctl_down(struct ipc_namespace *ns, int semid,
+ int cmd, int version, union semun arg)
{
    struct sem_array *sma;
    int err;
@@ -974,7 +974,7 @@ asmlinkage long sys_semctl (int semid, i
    return err;
    case IPC_RMID:
    case IPC_SET:
-    err = semctl_down(ns,semid,semnum,cmd,version,arg);
+    err = semctl_down(ns, semid, cmd, version, arg);
    return err;
    default:
        return -EINVAL;
```

--  
Pierre Peiffer

---

Containers mailing list

[Containers@lists.linux-foundation.org](mailto:Containers@lists.linux-foundation.org)

<https://lists.linux-foundation.org/mailman/listinfo/containers>

---