
Subject: [PATCH 16/17] [NETNS]: Enable IPv4 address manipulations inside namespace.

Posted by [den](#) on Wed, 06 Feb 2008 10:53:36 GMT

[View Forum Message](#) <> [Reply to Message](#)

Signed-off-by: Denis V. Lunev <den@openvz.org>

```
---
net/ipv4/devinet.c | 9 -----
1 files changed, 0 insertions(+), 9 deletions(-)

diff --git a/net/ipv4/devinet.c b/net/ipv4/devinet.c
index f7e78b7..aa23d10 100644
--- a/net/ipv4/devinet.c
+++ b/net/ipv4/devinet.c
@@ -446,9 +446,6 @@ static int inet_rtm_deladdr(struct sk_buff *skb, struct nlmsg_hdr *nlh, void
*arg

    ASSERT_RTNL();

- if (net != &init_net)
- return -EINVAL;
-
    err = nlmsg_parse(nlh, sizeof(*ifm), tb, IFA_MAX, ifa_ipv4_policy);
    if (err < 0)
        goto errout;
@@ -560,9 +557,6 @@ static int inet_rtm_newaddr(struct sk_buff *skb, struct nlmsg_hdr *nlh, void
*arg

    ASSERT_RTNL();

- if (net != &init_net)
- return -EINVAL;
-
    ifa = rtm_to_ifaddr(net, nlh);
    if (IS_ERR(ifa))
        return PTR_ERR(ifa);
@@ -1169,9 +1163,6 @@ static int inet_dump_ifaddr(struct sk_buff *skb, struct netlink_callback
*cb)
    struct in_ifaddr *ifa;
    int s_ip_idx, s_idx = cb->args[0];

- if (net != &init_net)
- return 0;
-
    s_ip_idx = ip_idx = cb->args[1];
    idx = 0;
    for_each_netdev(net, dev) {
--
```

1.5.3.rc5
