
Subject: [PATCH 14/17] [NETNS]: Process devinet_ioctl in the correct namespace.
Posted by [den](#) on Wed, 06 Feb 2008 10:53:34 GMT
[View Forum Message](#) <> [Reply to Message](#)

Add namespace parameter to devinet_ioctl and locate device inside it for a state changes.

Signed-off-by: Denis V. Lunev <den@openvz.org>

```
---
include/linux/inetdevice.h | 2 +-
net/ipv4/af_inet.c         | 7 ++++---
net/ipv4/devinet.c         | 6 +++---
net/ipv4/ipconfig.c        | 2 +-
4 files changed, 9 insertions(+), 8 deletions(-)

diff --git a/include/linux/inetdevice.h b/include/linux/inetdevice.h
index fc4e3db..da05ab4 100644
--- a/include/linux/inetdevice.h
+++ b/include/linux/inetdevice.h
@@ -129,7 +129,7 @@ extern int unregister_inetaddr_notifier(struct notifier_block *nb);

extern struct net_device *ip_dev_find(struct net *net, __be32 addr);
extern int inet_addr_onlink(struct in_device *in_dev, __be32 a, __be32 b);
-extern int devinet_ioctl(unsigned int cmd, void __user *);
+extern int devinet_ioctl(struct net *net, unsigned int cmd, void __user *);
extern void devinet_init(void);
extern struct in_device *inetdev_by_index(struct net *, int);
extern __be32 inet_select_addr(const struct net_device *dev, __be32 dst, int scope);
diff --git a/net/ipv4/af_inet.c b/net/ipv4/af_inet.c
index 09ca529..c270080 100644
--- a/net/ipv4/af_inet.c
+++ b/net/ipv4/af_inet.c
@@ -784,6 +784,7 @@ int inet_ioctl(struct socket *sock, unsigned int cmd, unsigned long arg)
{
    struct sock *sk = sock->sk;
    int err = 0;
+    struct net *net = sk->sk_net;

    switch (cmd) {
    case SIOCGSTAMP:
@@ -795,12 +795,12 @@ int inet_ioctl(struct socket *sock, unsigned int cmd, unsigned long arg)
    case SIOCADDRT:
    case SIOCDELRT:
    case SIOCRTMSG:
-    err = ip_rt_ioctl(sk->sk_net, cmd, (void __user *)arg);
+    err = ip_rt_ioctl(net, cmd, (void __user *)arg);
    break;
    case SIOCDDARP:

```

```

    case SIOCGARP:
    case SIOCSARP:
-   err = arp_ioctl(sk->sk_net, cmd, (void __user *)arg);
+   err = arp_ioctl(net, cmd, (void __user *)arg);
    break;
    case SIOCGIFADDR:
    case SIOCSIFADDR:
@@ -813,7 +814,7 @@ int inet_ioctl(struct socket *sock, unsigned int cmd, unsigned long arg)
    case SIOCSIFPFLAGS:
    case SIOCGIFPFLAGS:
    case SIOCSIFFLAGS:
-   err = devinet_ioctl(cmd, (void __user *)arg);
+   err = devinet_ioctl(net, cmd, (void __user *)arg);
    break;
    default:
        if (sk->sk_prot->ioctl)
diff --git a/net/ipv4/devinet.c b/net/ipv4/devinet.c
index f282b26..a06fcae 100644
--- a/net/ipv4/devinet.c
+++ b/net/ipv4/devinet.c
@@ -595,7 +595,7 @@ static __inline__ int inet_abc_len(__be32 addr)
}

```

```

-int devinet_ioctl(unsigned int cmd, void __user *arg)
+int devinet_ioctl(struct net *net, unsigned int cmd, void __user *arg)
{
    struct ifreq ifr;
    struct sockaddr_in sin_orig;
@@ -624,7 +624,7 @@ int devinet_ioctl(unsigned int cmd, void __user *arg)
    *colon = 0;

```

```

#ifdef CONFIG_KMOD
- dev_load(&init_net, ifr.ifr_name);
+ dev_load(net, ifr.ifr_name);
#endif

```

```

    switch (cmd) {
@@ -665,7 +665,7 @@ int devinet_ioctl(unsigned int cmd, void __user *arg)
    rtnl_lock();

```

```

    ret = -ENODEV;
- if ((dev = __dev_get_by_name(&init_net, ifr.ifr_name)) == NULL)
+ if ((dev = __dev_get_by_name(net, ifr.ifr_name)) == NULL)
    goto done;

```

```

    if (colon)
diff --git a/net/ipv4/ipconfig.c b/net/ipv4/ipconfig.c

```

index a52b585..009d78f 100644

--- a/net/ipv4/ipconfig.c

+++ b/net/ipv4/ipconfig.c

@@ -291,7 +291,7 @@ static int __init ic_dev_ioctl(unsigned int cmd, struct ifreq *arg)

 mm_segment_t oldfs = get_fs();

 set_fs(get_ds());

- res = devinet_ioctl(cmd, (struct ifreq __user *) arg);

+ res = devinet_ioctl(&init_net, cmd, (struct ifreq __user *) arg);

 set_fs(oldfs);

 return res;

}

--

1.5.3.rc5
