
Subject: Re: [PATCH] [IPV4]: Remove warning in node_set_parent.

Posted by [den](#) on Tue, 12 Feb 2008 08:11:58 GMT

[View Forum Message](#) <> [Reply to Message](#)

ugly :), but

Acked-by: Denis V. Lunev <den@openvz.org>

On Mon, 2008-02-11 at 11:48 -0800, Stephen Hemminger wrote:

> On Mon, 11 Feb 2008 11:47:17 +0300

> "Denis V. Lunev" <den@openvz.org> wrote:

>
>> net/ipv4/fib_trie.c: In function 'node_set_parent':
>> net/ipv4/fib_trie.c:184: warning: assignment makes integer from pointer
>> without a cast
>>
>> Signed-off-by: Denis V. Lunev <den@openvz.org>
>> ---
>> net/ipv4/fib_trie.c | 7 +++++---
>> 1 files changed, 4 insertions(+), 3 deletions(-)
>>
>> diff --git a/net/ipv4/fib_trie.c b/net/ipv4/fib_trie.c
>> index f5fba3f..1753cd4 100644
>> --- a/net/ipv4/fib_trie.c
>> +++ b/net/ipv4/fib_trie.c
>> @@ -177,10 +177,11 @@ static inline struct tnode *node_parent_rcu(struct node *node)
>> return rcu_dereference(ret);
>> }
>>
>> -static inline void node_set_parent(struct node *node, struct tnode *ptr)
>> +static inline void node_set_parent(struct node *node, struct tnode *__ptr)
>> {
>> - rcu_assign_pointer(node->parent,
>> - (unsigned long)ptr | NODE_TYPE(node));
>> + struct node *ptr;
>> + ptr = (struct node *)((unsigned long)__ptr | NODE_TYPE(node));
>> + rcu_assign_pointer(node->parent, ptr);
>> }
>>
>> static inline struct node *tnode_get_child(struct tnode *tn, unsigned int i)
>
> No, this causes new warning from assigning pointer (ptr) to integer node->parent.
>
> Why not just change rcupdate.h to do the right thing.
>
>> From [a00f7cbf1c2f2282eced236e1e8b99b0fec213a](#) Mon Sep 17 00:00:00 2001
> From: Stephen Hemminger <stephen.hemminger@vyatta.com>
> Date: Mon, 11 Feb 2008 11:28:13 -0800

```

> Subject: [PATCH] eliminate warnings when rcu_assign_pointer is used with unsigned long
>
> It is reasonable to use RCU with non-pointer values, and describe
> the optimization.
>
> Signed-off-by: Stephen Hemminger <shemminger@vyatta.com>
> ---
> include/linux/rcupdate.h | 13 ++++++-----
> 1 files changed, 7 insertions(+), 6 deletions(-)
>
> diff --git a/include/linux/rcupdate.h b/include/linux/rcupdate.h
> index 37a642c..c44ac87 100644
> --- a/include/linux/rcupdate.h
> +++ b/include/linux/rcupdate.h
> @@ -172,14 +172,15 @@ struct rcu_head {
>  * structure after the pointer assignment. More importantly, this
>  * call documents which pointers will be dereferenced by RCU read-side
>  * code.
>  + *
>  + * If value is the NULL (constant 0), then no barrier is needed.
>  */
>
> -#define rcu_assign_pointer(p, v) \
> - ({ \
> - if (!__builtin_constant_p(v) || \
> -     ((v) != NULL)) \
> -     smp_wmb(); \
> - (p) = (v); \
> +#define rcu_assign_pointer(p, v) \
> + ({ \
> + if (!__builtin_constant_p(v) && v) \
> +     smp_wmb(); \
> + (p) = (v); \
> })
>
> /**
> --
> 1.5.3.8
>
>
>
>

```
