
Subject: Re: [RFC][PATCH 7/7] CGroup API: Update cpusets to use cgroup structured file API

Posted by [Paul Menage](#) on Sun, 17 Feb 2008 17:18:44 GMT

[View Forum Message](#) <> [Reply to Message](#)

On Feb 16, 2008 7:29 PM, Paul Jackson <pj@sgi.com> wrote:

>
> From: Paul Jackson <pj@sgi.com>
>
> Strip all trailing whitespace (such as carriage returns)
> when parsing integer writes to cgroup files, not just
> one trailing newline if present.

Sounds like a good idea to me. Thanks for this.

>
> Signed-off-by: Paul Jackson <pj@sgi.com>
> Cc: Paul Menage <menage@google.com>

Acked-by: Paul Menage <menage@google.com>

>
> ---
> kernel/cgroup.c | 5 +----
> 1 file changed, 1 insertion(+), 4 deletions(-)
>
> --- 2.6.24-mm1.orig/kernel/cgroup.c 2008-02-16 04:20:33.000000000 -0800
> +++ 2.6.24-mm1/kernel/cgroup.c 2008-02-16 19:00:41.207478218 -0800
> @@ -1321,10 +1321,7 @@ static ssize_t cgroup_write_uint(struct
> return -EFAULT;
>
> buffer[nbytes] = 0; /* nul-terminate */
> -
> - /* strip newline if necessary */
> - if (nbytes && (buffer[nbytes-1] == '\n'))
> - buffer[nbytes-1] = 0;
> + stripslashes(buffer); /* strip -just- trailing whitespace */
> val = simple_strtoul(buffer, &end, 0);
> if (*end)
> return -EINVAL;
>
>
> --
>
> I won't rest till it's the best ...
> Programmer, Linux Scalability
> Paul Jackson <pj@sgi.com> 1.940.382.4214
>

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
