
Subject: [PATCH 3/3] memcgroup: return negative error code in
mem_cgroup_create()

Posted by [Li Zefan](#) on Mon, 18 Feb 2008 05:59:37 GMT

[View Forum Message](#) <> [Reply to Message](#)

Cgroup requires the subsystem to return negative error code on
error in the create method.

Signed-off-by: Li Zefan <lizf@cn.fujitsu.com>

Acked-by: KAMEZAWA Hiroyuki <kamezawa.hiroyu@jp.fujitsu.com>

mm/memcontrol.c | 4 ++--

1 files changed, 2 insertions(+), 2 deletions(-)

diff --git a/mm/memcontrol.c b/mm/memcontrol.c

index c2959ee..4aac04c 100644

--- a/mm/memcontrol.c

+++ b/mm/memcontrol.c

@@ -1101,7 +1101,7 @@ mem_cgroup_create(struct cgroup_subsys *ss, struct cgroup *cont)
 mem = kzalloc(sizeof(struct mem_cgroup), GFP_KERNEL);

if (mem == NULL)
- return NULL;
+ return ERR_PTR(-ENOMEM);

res_counter_init(&mem->res);

@@ -1117,7 +1117,7 @@ free_out:
 free_mem_cgroup_per_zone_info(mem, node);
 if (cont->parent != NULL)
 kfree(mem);
- return NULL;
+ return ERR_PTR(-ENOMEM);
}

static void mem_cgroup_pre_destroy(struct cgroup_subsys *ss,

--

1.5.4.rc3

Containers mailing list

Containers@lists.linux-foundation.org

<https://lists.linux-foundation.org/mailman/listinfo/containers>
