
Subject: [PATCH 13/17 net-2.6.26] [NETNS]: Register /proc/net/route for each namespace.

Posted by [den](#) on Tue, 19 Feb 2008 07:31:33 GMT

[View Forum Message](#) <> [Reply to Message](#)

Signed-off-by: Denis V. Lunev <den@openvz.org>

net/ipv4/route.c | 24 ++++++

1 files changed, 21 insertions(+), 3 deletions(-)

diff --git a/net/ipv4/route.c b/net/ipv4/route.c

index c11e6bf..5f67eba 100644

--- a/net/ipv4/route.c

+++ b/net/ipv4/route.c

```
@@ -545,7 +545,7 @@ static int ip_rt_acct_read(char *buffer, char **start, off_t offset,
 }
#endif
```

```
-static __init int ip_rt_proc_init(struct net *net)
```

```
+static int __net_init ip_rt_do_proc_init(struct net *net)
```

```
{
    struct proc_dir_entry *pde;
```

```
@@ -577,8 +577,26 @@ err2:
```

```
err1:
```

```
    return -ENOMEM;
```

```
}
```

```
+
```

```
+static void __net_exit ip_rt_do_proc_exit(struct net *net)
```

```
+{
```

```
+ remove_proc_entry("rt_cache", net->proc_net_stat);
```

```
+ remove_proc_entry("rt_cache", net->proc_net);
```

```
+ remove_proc_entry("rt_acct", net->proc_net);
```

```
+}
```

```
+
```

```
+static struct pernet_operations ip_rt_proc_ops __net_initdata = {
```

```
+ .init = ip_rt_do_proc_init,
```

```
+ .exit = ip_rt_do_proc_exit,
```

```
+};
```

```
+
```

```
+static int __init ip_rt_proc_init(void)
```

```
+{
```

```
+ return register_pernet_subsys(&ip_rt_proc_ops);
```

```
+}
```

```
+
```

```
#else
```

```
-static inline int ip_rt_proc_init(struct net *net)
```

```
+static inline int ip_rt_proc_init(void)
```

```
{
    return 0;
}
@@ -3056,7 +3074,7 @@ int __init ip_rt_init(void)
    ip_rt_secret_interval;
    add_timer(&rt_secret_timer);

- if (ip_rt_proc_init(&init_net))
+ if (ip_rt_proc_init())
    printk(KERN_ERR "Unable to create route proc files\n");
#ifdef CONFIG_XFRM
    xfrm_init();
--
1.5.3.rc5
```
