
Subject: [PATCH 7/17 net-2.6.26] [NETNS]: Disable multicaststing configuration inside non-initial namespace.

Posted by [den](#) on Tue, 19 Feb 2008 07:31:27 GMT

[View Forum Message](#) <> [Reply to Message](#)

Do not calls hooks from device notifiers and disallow configuration from ioctl/netlink layer.

Signed-off-by: Denis V. Lunev <den@openvz.org>

net/ipv4/igmp.c | 39 ++++++
1 files changed, 39 insertions(+), 0 deletions(-)

```
diff --git a/net/ipv4/igmp.c b/net/ipv4/igmp.c
index 732cd07..d3f34a7 100644
--- a/net/ipv4/igmp.c
+++ b/net/ipv4/igmp.c
@@ -1198,6 +1198,9 @@ void ip_mc_inc_group(struct in_device *in_dev, __be32 addr)
```

 ASSERT_RTNL();

```
+ if (in_dev->dev->nd_net != &init_net)
+ return;
+
for (im=in_dev->mc_list; im; im=im->next) {
    if (im->multiaddr == addr) {
        im->users++;
@@ -1277,6 +1280,9 @@ void ip_mc_dec_group(struct in_device *in_dev, __be32 addr)
```

 ASSERT_RTNL();

```
+ if (in_dev->dev->nd_net != &init_net)
+ return;
+
for (ip=&in_dev->mc_list; (i=*ip)!=NULL; ip=&i->next) {
    if (i->multiaddr==addr) {
        if (--i->users == 0) {
@@ -1304,6 +1310,9 @@ void ip_mc_down(struct in_device *in_dev)
```

 ASSERT_RTNL();

```
+ if (in_dev->dev->nd_net != &init_net)
+ return;
+
for (i=in_dev->mc_list; i; i=i->next)
    igmp_group_dropped(i);

@@ -1324,6 +1333,9 @@ void ip_mc_init_dev(struct in_device *in_dev)
```

```

{
    ASSERT_RTNL();

+ if (in_dev->dev->nd_net != &init_net)
+     return;
+
    in_dev->mc_tomb = NULL;
#ifndef CONFIG_IP_MULTICAST
    in_dev->mr_gq_running = 0;
@@ -1347,6 +1359,9 @@ void ip_mc_up(struct in_device *in_dev)

    ASSERT_RTNL();

+ if (in_dev->dev->nd_net != &init_net)
+     return;
+
    ip_mc_inc_group(in_dev, IGMP_ALL_HOSTS);

    for (i=in_dev->mc_list; i; i=i->next)
@@ -1363,6 +1378,9 @@ void ip_mc_destroy_dev(struct in_device *in_dev)

    ASSERT_RTNL();

+ if (in_dev->dev->nd_net != &init_net)
+     return;
+
/* Deactivate timers */
    ip_mc_down(in_dev);

@@ -1744,6 +1762,9 @@ int ip_mc_join_group(struct sock *sk , struct ip_mreqn *imr)
    if (!ipv4_is_multicast(addr))
        return -EINVAL;

+ if (sk->sk_net != &init_net)
+     return -EPROTONOSUPPORT;
+
    rtnl_lock();

    in_dev = ip_mc_find_dev(imr);
@@ -1812,6 +1833,9 @@ int ip_mc_leave_group(struct sock *sk, struct ip_mreqn *imr)
    u32 ifindex;
    int ret = -EADDRNOTAVAIL;

+ if (sk->sk_net != &init_net)
+     return -EPROTONOSUPPORT;
+
    rtnl_lock();
    in_dev = ip_mc_find_dev(imr);

```

```

ifindex = imr->imr_ifindex;
@@ -1857,6 +1881,9 @@ int ip_mc_source(int add, int omode, struct sock *sk, struct
    if (!ipv4_is_multicast(addr))
        return -EINVAL;

+ if (sk->sk_net != &init_net)
+     return -EPROTONOSUPPORT;
+
    rtnl_lock();

    imr.imr_multiaddr.s_addr = mreqs->imr_multiaddr;
@@ -1990,6 +2017,9 @@ int ip_mc_msfilter(struct sock *sk, struct ip_msfilter *msf, int ifindex
    msf->imsf_fmode != MCAST_EXCLUDE)
    return -EINVAL;

+ if (sk->sk_net != &init_net)
+     return -EPROTONOSUPPORT;
+
    rtnl_lock();

    imr.imr_multiaddr.s_addr = msf->imsf_multiaddr;
@@ -2070,6 +2100,9 @@ int ip_mc_msfilterget(struct sock *sk, struct ip_msfilter *msf,
    if (!ipv4_is_multicast(addr))
        return -EINVAL;

+ if (sk->sk_net != &init_net)
+     return -EPROTONOSUPPORT;
+
    rtnl_lock();

    imr.imr_multiaddr.s_addr = msf->imsf_multiaddr;
@@ -2132,6 +2165,9 @@ int ip_mc_gsfget(struct sock *sk, struct group_filter *gsf,
    if (!ipv4_is_multicast(addr))
        return -EINVAL;

+ if (sk->sk_net != &init_net)
+     return -EPROTONOSUPPORT;
+
    rtnl_lock();

    err = -EADDRNOTAVAIL;
@@ -2216,6 +2252,9 @@ void ip_mc_drop_socket(struct sock *sk)
    if (inet->mc_list == NULL)
        return;

+ if (sk->sk_net != &init_net)
+     return;
+

```

```
rtnl_lock();
while ((iml = inet->mc_list) != NULL) {
    struct in_device *in_dev;
```

--
1.5.3.rc5
