
Subject: Re: [PATCH 6/7] cgroup: remove duplicate code in find_css_set()

Posted by [Paul Menage](#) on Wed, 20 Feb 2008 03:02:35 GMT

[View Forum Message](#) <> [Reply to Message](#)

On Feb 17, 2008 9:49 PM, Li Zefan <lizf@cn.fujitsu.com> wrote:

> The list head res->tasks gets initialized twice in find_css_set().

>

> Signed-off-by: Li Zefan <lizf@cn.fujitsu.com>

Acked-by: Paul Menage <menage@google.com>

> ---

> kernel/cgroup.c | 1 -

> 1 files changed, 0 insertions(+), 1 deletions(-)

>

> diff --git a/kernel/cgroup.c b/kernel/cgroup.c

> index e8c8e58..71cf961 100644

> --- a/kernel/cgroup.c

> +++ b/kernel/cgroup.c

> @@ -473,7 +473,6 @@ static struct css_set *find_css_set(

> /* Link this cgroup group into the list */

> list_add(&res->list, &init_css_set.list);

> css_set_count++;

> - INIT_LIST_HEAD(&res->tasks);

> write_unlock(&css_set_lock);

>

> return res;

> --

> 1.5.4.rc3

>

>

Containers mailing list

Containers@lists.linux-foundation.org

<https://lists.linux-foundation.org/mailman/listinfo/containers>
