

---

Subject: [PATCH 01/10] CGroup API files: Rename read/write\_uint methods to read\_write\_u64

Posted by [Paul Menage](#) on Sat, 23 Feb 2008 22:47:26 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Several people have justifiably complained that the "\_uint" suffix is inappropriate for functions that handle u64 values, so this patch just renames all these functions and their users to have the suffic \_u64.

Signed-off-by: Paul Menage <[menage@google.com](mailto:menage@google.com)>

---

```
include/linux/cgroup.h |  8 ++++++-
kernel/cgroup.c       | 32 ++++++-----+
kernel/cgroup_debug.c |  8 ++++++-
kernel/sched.c        | 18 ++++++-----+
4 files changed, 33 insertions(+), 33 deletions(-)
```

Index: cgroup-2.6.25-rc2-mm1/include/linux/cgroup.h

```
=====
--- cgroup-2.6.25-rc2-mm1.orig/include/linux/cgroup.h
+++ cgroup-2.6.25-rc2-mm1/include/linux/cgroup.h
@@ -190,20 +190,20 @@ struct cftype {
    struct file *file,
    char __user *buf, size_t nbytes, loff_t *ppos);
 /*
- * read_uint() is a shortcut for the common case of returning a
+ * read_u64() is a shortcut for the common case of returning a
 * single integer. Use it in place of read()
 */
- u64 (*read_uint) (struct cgroup *cont, struct cftype *cft);
+ u64 (*read_u64) (struct cgroup *cont, struct cftype *cft);
 ssize_t (*write) (struct cgroup *cont, struct cftype *cft,
    struct file *,
    const char __user *buf, size_t nbytes, loff_t *ppos);

 /*
- * write_uint() is a shortcut for the common case of accepting
+ * write_u64() is a shortcut for the common case of accepting
 * a single integer (as parsed by simple_strtoull) from
 * userspace. Use in place of write(); return 0 or error.
 */
- int (*write_uint) (struct cgroup *cont, struct cftype *cft, u64 val);
+ int (*write_u64) (struct cgroup *cont, struct cftype *cft, u64 val);

 int (*release) (struct inode *inode, struct file *file);
};
```

Index: cgroup-2.6.25-rc2-mm1/kernel/cgroup.c

```
=====
--- cgroup-2.6.25-rc2-mm1.orig/kernel/cgroup.c
+++ cgroup-2.6.25-rc2-mm1/kernel/cgroup.c
@@ -1303,10 +1303,10 @@ enum cgroup_filetype {
    FILE_RELEASE_AGENT,
};

-static ssize_t cgroup_write_uint(struct cgroup *cgrp, struct ctype *cft,
-    struct file *file,
-    const char __user *userbuf,
-    size_t nbytes, loff_t *unused_ppos)
+static ssize_t cgroup_write_u64(struct cgroup *cgrp, struct ctype *cft,
+    struct file *file,
+    const char __user *userbuf,
+    size_t nbytes, loff_t *unused_ppos)
{
    char buffer[64];
    int retval = 0;
@@ -1330,7 +1330,7 @@ static ssize_t cgroup_write_uint(struct
    return -EINVAL;

/* Pass to subsystem */
- retval = cft->write_uint(cgrp, cft, val);
+ retval = cft->write_u64(cgrp, cft, val);
if (!retval)
    retval = nbytes;
return retval;
@@ -1411,18 +1411,18 @@ static ssize_t cgroup_file_write(struct
    return -ENODEV;
if (cft->write)
    return cft->write(cgrp, cft, file, buf, nbytes, ppos);
- if (cft->write_uint)
-    return cgroup_write_uint(cgrp, cft, file, buf, nbytes, ppos);
+ if (cft->write_u64)
+    return cgroup_write_u64(cgrp, cft, file, buf, nbytes, ppos);
    return -EINVAL;
}

-static ssize_t cgroup_read_uint(struct cgroup *cgrp, struct ctype *cft,
-    struct file *file,
-    char __user *buf, size_t nbytes,
-    loff_t *ppos)
+static ssize_t cgroup_read_u64(struct cgroup *cgrp, struct ctype *cft,
+    struct file *file,
+    char __user *buf, size_t nbytes,
+    loff_t *ppos)
{
    char tmp[64];
```

```

- u64 val = cft->read_uint(cgrp, cft);
+ u64 val = cft->read_u64(cgrp, cft);
int len = sprintf(tmp, "%llu\n", (unsigned long long) val);

return simple_read_from_buffer(buf, nbytes, ppos, tmp, len);
@@ -1482,8 +1482,8 @@ static ssize_t cgroup_file_read(struct f

if (cft->read)
    return cft->read(cgrp, cft, file, buf, nbytes, ppos);
- if (cft->read_uint)
-    return cgroup_read_uint(cgrp, cft, file, buf, nbytes, ppos);
+ if (cft->read_u64)
+    return cgroup_read_u64(cgrp, cft, file, buf, nbytes, ppos);
    return -EINVAL;
}

```

```
@@ -2141,14 +2141,14 @@ static struct cftype files[] = {
```

```
{
    .name = "notify_on_release",
-   .read_uint = cgroup_read_notify_on_release,
+   .read_u64 = cgroup_read_notify_on_release,
    .write = cgroup_common_file_write,
    .private = FILE_NOTIFY_ON_RELEASE,
},
{

    .name = "releasable",
-   .read_uint = cgroup_read_releasable,
+   .read_u64 = cgroup_read_releasable,
    .private = FILE_RELEASEABLE,
}
};
```

```
Index: cgroup-2.6.25-rc2-mm1/kernel/cgroup_debug.c
```

---

```
--- cgroup-2.6.25-rc2-mm1.orig/kernel/cgroup_debug.c
+++ cgroup-2.6.25-rc2-mm1/kernel/cgroup_debug.c
@@ -65,21 +65,21 @@ static u64 current_css_set_refcount_read
static struct cftype files[] = {
{
    .name = "cgroup_refcount",
-   .read_uint = cgroup_refcount_read,
+   .read_u64 = cgroup_refcount_read,
},
{
    .name = "taskcount",
-   .read_uint = taskcount_read,
+   .read_u64 = taskcount_read,
```

```

},
{
  .name = "current_css_set",
- .read_uint = current_css_set_read,
+ .read_u64 = current_css_set_read,
},
{
  .name = "current_css_set_refcount",
- .read_uint = current_css_set_refcount_read,
+ .read_u64 = current_css_set_refcount_read,
},
};

```

Index: cgroup-2.6.25-rc2-mm1/kernel/sched.c

---

--- cgroup-2.6.25-rc2-mm1.orig/kernel/sched.c

+++ cgroup-2.6.25-rc2-mm1/kernel/sched.c  
@@ -8286,13 +8286,13 @@ cpu\_cgroup\_attach(struct cgroup\_subsys \*

}

```
#ifdef CONFIG_FAIR_GROUP_SCHED
-static int cpu_shares_write_uint(struct cgroup *cgrp, struct cftype *cftype,
+static int cpu_shares_write_u64(struct cgroup *cgrp, struct cftype *cftype,
    u64 shareval)
{
    return sched_group_set_shares(cgroup_tg(cgrp), shareval);
}
```

```
-static u64 cpu_shares_read_uint(struct cgroup *cgrp, struct cftype *cft)
+static u64 cpu_shares_read_u64(struct cgroup *cgrp, struct cftype *cft)
{
    struct task_group *tg = cgroup_tg(cgrp);
```

```
@@ -8346,13 +8346,13 @@ static ssize_t cpu_rt_runtime_read(struc
    return simple_read_from_buffer(buf, nbytes, ppos, tmp, len);
}
```

```
-static int cpu_rt_period_write_uint(struct cgroup *cgrp, struct cftype *cftype,
+static int cpu_rt_period_write_u64(struct cgroup *cgrp, struct cftype *cftype,
    u64 rt_period_us)
{
    return sched_group_set_rt_period(cgroup_tg(cgrp), rt_period_us);
}
```

```
-static u64 cpu_rt_period_read_uint(struct cgroup *cgrp, struct cftype *cft)
+static u64 cpu_rt_period_read_u64(struct cgroup *cgrp, struct cftype *cft)
```

```

{
    return sched_group_rt_period(cgroup_tg(cgrp));
}
@@ -8362,8 +8362,8 @@ static struct cftype cpu_files[] = {
#endif CONFIG_FAIR_GROUP_SCHED
{
    .name = "shares",
-   .read_uint = cpu_shares_read_uint,
-   .write_uint = cpu_shares_write_uint,
+   .read_u64 = cpu_shares_read_u64,
+   .write_u64 = cpu_shares_write_u64,
},
#endif
#ifndef CONFIG_RT_GROUP_SCHED
@@ -8374,8 +8374,8 @@ static struct cftype cpu_files[] = {
},
{
    .name = "rt_period_us",
-   .read_uint = cpu_rt_period_read_uint,
-   .write_uint = cpu_rt_period_write_uint,
+   .read_u64 = cpu_rt_period_read_u64,
+   .write_u64 = cpu_rt_period_write_u64,
},
#endif
};
@@ -8483,7 +8483,7 @@ static u64 cpuusage_read(struct cgroup *
static struct cftype files[] = {
{
    .name = "usage",
-   .read_uint = cpuusage_read,
+   .read_u64 = cpuusage_read,
},
};

--
```

---

Containers mailing list  
 Containers@lists.linux-foundation.org  
<https://lists.linux-foundation.org/mailman/listinfo/containers>

---