

---

Subject: [PATCH 07/10] CGroup API files: Use cgroup map for memcontrol stats file  
Posted by [Paul Menage](#) on Sat, 23 Feb 2008 22:47:32 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Remove the seq\_file boilerplate used to construct the memcontrol stats map, and instead use the new map representation for cgroup control files

Signed-off-by: Paul Menage <[menage@google.com](mailto:menage@google.com)>

---

mm/memcontrol.c | 30 +++++-----  
1 file changed, 6 insertions(+), 24 deletions(-)

Index: cgroup-2.6.25-rc2-mm1/mm/memcontrol.c

```
=====
--- cgroup-2.6.25-rc2-mm1.orig/mm/memcontrol.c
+++ cgroup-2.6.25-rc2-mm1/mm/memcontrol.c
@@ -971,9 +971,9 @@ static const struct mem_cgroup_stat_desc
 [MEM_CGROUP_STAT_RSS] = { "rss", PAGE_SIZE, },
};

-static int mem_control_stat_show(struct seq_file *m, void *arg)
+static int mem_control_stat_show(struct cgroup *cont, struct cftype *cft,
+    struct cgroup_map_cb *cb)
{
- struct cgroup *cont = m->private;
    struct mem_cgroup *mem_cont = mem_cgroup_from_cont(cont);
    struct mem_cgroup_stat *stat = &mem_cont->stat;
    int i;
@@ -983,8 +983,7 @@ static int mem_control_stat_show(struct

    val = mem_cgroup_read_stat(stat, i);
    val *= mem_cgroup_stat_desc[i].unit;
- seq_printf(m, "%s %lld\n", mem_cgroup_stat_desc[i].msg,
-   (long long)val);
+ cb->fill(cb, mem_cgroup_stat_desc[i].msg, val);
}
/* showing # of active pages */
{
@@ -994,29 +993,12 @@ static int mem_control_stat_show(struct
    MEM_CGROUP_ZSTAT_INACTIVE);
    active = mem_cgroup_get_all_zonestat(mem_cont,
        MEM_CGROUP_ZSTAT_ACTIVE);
- seq_printf(m, "active %ld\n", (active) * PAGE_SIZE);
- seq_printf(m, "inactive %ld\n", (inactive) * PAGE_SIZE);
+ cb->fill(cb, "active", (active) * PAGE_SIZE);
+ cb->fill(cb, "inactive", (inactive) * PAGE_SIZE);
```

```

    }
    return 0;
}

static const struct file_operations mem_control_stat_file_operations = {
    .read = seq_read,
    .llseek = seq_llseek,
    .release = single_release,
};

static int mem_control_stat_open(struct inode *unused, struct file *file)
{
    /* XXX __d_cont */
    struct cgroup *cont = file->f_dentry->d_parent->d_fsdma;
    file->f_op = &mem_control_stat_file_operations;
    return single_open(file, mem_control_stat_show, cont);
}

static struct cftype mem_cgroup_files[] = {
{
    .name = "usage_in_bytes",
@@ -1041,7 +1023,7 @@ static struct cftype mem_cgroup_files[]
},
{
    .name = "stat",
    .open = mem_control_stat_open,
+    .read_map = mem_control_stat_show,
},
};

--
```

---

Containers mailing list  
 Containers@lists.linux-foundation.org  
<https://lists.linux-foundation.org/mailman/listinfo/containers>

---