
Posted by [piavlo](#) on Thu, 06 Mar 2008 20:01:45 GMT

[View Forum Message](#) <> [Reply to Message](#)

Quote:

```
cs-ovz1 ~ # cat /etc/vz/vznet.conf
#!/bin/bash
```

```
EXTERNAL_SCRIPT="/etc/vz/bin/vzbridge.add"
cs-ovz1 ~ # cat /etc/vz/bin/vzbridge.add
#!/bin/bash
```

```
CONFIGFILE=/etc/vz/conf/$VEID.conf
. $CONFIGFILE
VZHOSTIF=`echo $NETIF |sed 's/^. *host_ifname=\\(.*)\\. *$/\\1/g`
```

```
if [ ! -n "$VZHOSTIF" ]; then
    echo "According to $CONFIGFILE VE$VEID has no veth interface configured."
    exit 1
fi
```

```
if [ ! -n "$BRIDGEDEV" ]; then
    echo "According to $CONFIGFILE VE$VEID veth interface is not enslaved to any bridge."
    exit 1
fi
```

```
ifconfig veth${VEID}.0 0
brctl addif ${BRIDGEDEV} veth${VEID}.0
exit $?
cs-ovz1 ~ # fgrep BRIDGEDEV /etc/vz/conf/103.conf
```

BRIDGEDEV="br0"

cs-ovz1 ~ # brctl show

bridge name	bridge id	STP enabled	interfaces
br0	8000.0002b3355dc7	no	eth0
			veth1000.0
			veth103.0
			veth104.0

cs-ovz1 ~ #

inspired by http://wiki.openvz.org/Veth#Making_a_bridged_veth-device_persistent
