

---

Subject: [PATCH 2/3] [IPV6]: inet6\_dev on loopback should be kept until namespace stop.

Posted by [den](#) on Tue, 18 Mar 2008 14:35:24 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

In the other case it will be destroyed when last address will be removed from lo inside a namespace. This will break IPv6 in several places. The most obvious one is ip6\_dst\_ifdown.

Signed-off-by: Denis V. Lunev <[den@openvz.org](mailto:den@openvz.org)>

---

net/ipv6/addrconf.c | 2 +-  
1 files changed, 1 insertions(+), 1 deletions(-)

diff --git a/net/ipv6/addrconf.c b/net/ipv6/addrconf.c

index d68e8f5..40784ea 100644

--- a/net/ipv6/addrconf.c

+++ b/net/ipv6/addrconf.c

@@ -2444,7 +2444,7 @@ static int addrconf\_ifdown(struct net\_device \*dev, int how)

ASSERT\_RTNL();

- if (dev == init\_net.loopback\_dev && how == 1)

+ if ((dev->flags & IFF\_LOOPBACK) && how == 1)

    how = 0;

    rt6\_ifdown(net, dev);

--

1.5.3.rc5

---

Containers mailing list

[Containers@lists.linux-foundation.org](mailto:Containers@lists.linux-foundation.org)

<https://lists.linux-foundation.org/mailman/listinfo/containers>

---