
Subject: [PATCH 10/11 net-2.6.26] [NETNS]: Allow to create sockets in non-initial namespace.

Posted by [den](#) on Mon, 24 Mar 2008 14:36:02 GMT

[View Forum Message](#) <> [Reply to Message](#)

Allow to create sockets in the namespace if the protocol ok with this.

Signed-off-by: Denis V. Lunev <den@openvz.org>

net/ipv4/af_inet.c | 24 ++++++-----
1 files changed, 21 insertions(+), 3 deletions(-)

```
diff --git a/net/ipv4/af_inet.c b/net/ipv4/af_inet.c
index a9e241c..39ddb84 100644
--- a/net/ipv4/af_inet.c
+++ b/net/ipv4/af_inet.c
@@ -243,6 +243,23 @@ void build_ehash_secret(void)
}
EXPORT_SYMBOL(build_ehash_secret);

+static inline int inet_netns_ok(struct net *net, int protocol)
+{
+ int hash;
+ struct net_protocol *ipprot;
+
+ if (net == &init_net)
+ return 1;
+
+ hash = protocol & (MAX_INET_PROTOS - 1);
+ ipprot = rcu_dereference(inet_protos[hash]);
+
+ if (ipprot == NULL)
+ /* raw IP is OK */
+ return 1;
+ return ipprot->netns_ok;
+}
+
/*
 * Create an inet socket.
 */
@@ -259,9 +276,6 @@ static int inet_create(struct net *net, struct socket *sock, int protocol)
int try_loading_module = 0;
int err;

- if (net != &init_net)
- return -EAFNOSUPPORT;
-
- if (sock->type != SOCK_RAW &&
```

```
sock->type != SOCK_DGRAM &&
!inet_ehash_secret)
@@ -320,6 +334,10 @@ lookup_protocol:
if (answer->capability > 0 && !capable(answer->capability))
    goto out_rcu_unlock;

+ err = -EAFNOSUPPORT;
+ if (!inet_netns_ok(net, protocol))
+     goto out_rcu_unlock;
+
    sock->ops = answer->ops;
    answer_prot = answer->prot;
    answer_no_check = answer->no_check;
--
```

1.5.3.rc5
