
Subject: [PATCH net-2.6.26 1/4][NETNS][ICMP]: Register pernet subsys to make ICMP sysctls per-net.

Posted by [Pavel Emelianov](#) on Wed, 26 Mar 2008 08:51:21 GMT

[View Forum Message](#) <> [Reply to Message](#)

This includes adding pernet_operations, empty init and exit hooks and a bit of changes in sysctl_ipv4_init just not to have this part in next patches.

Signed-off-by: Pavel Emelyanov <xemul@openvz.org>

net/ipv4/sysctl_net_ipv4.c | 24 ++++++
1 files changed, 23 insertions(+), 1 deletions(-)

diff --git a/net/ipv4/sysctl_net_ipv4.c b/net/ipv4/sysctl_net_ipv4.c

index 88286f3..c2fca30 100644

--- a/net/ipv4/sysctl_net_ipv4.c

+++ b/net/ipv4/sysctl_net_ipv4.c

@@ -811,12 +811,34 @@ struct ctl_path net_ipv4_ctl_path[] = {
};
EXPORT_SYMBOL_GPL(net_ipv4_ctl_path);

+static __net_init int ipv4_sysctl_init_net(struct net *net)

+{

+ return 0;

+}

+

+static __net_exit void ipv4_sysctl_exit_net(struct net *net)

+{

+}

+

+static __net_initdata struct pernet_operations ipv4_sysctl_ops = {

+ .init = ipv4_sysctl_init_net,

+ .exit = ipv4_sysctl_exit_net,

+};

+

static __init int sysctl_ipv4_init(void)

{

struct ctl_table_header *hdr;

hdr = register_sysctl_paths(net_ipv4_ctl_path, ipv4_table);

- return hdr == NULL ? -ENOMEM : 0;

+ if (hdr == NULL)

+ return -ENOMEM;

+

+ if (register_pernet_subsys(&ipv4_sysctl_ops)) {

+ unregister_sysctl_table(hdr);

```
+ return -ENOMEM;  
+ }  
+  
+ return 0;  
}
```

```
__initcall(sysctl_ipv4_init);
```

```
--
```

1.5.3.4
