
Subject: Re: OpenVZ and IP masquerading
Posted by [Santi](#) on Mon, 24 Apr 2006 14:42:23 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hello dev,

Command outputs, "xxx" == public IP address:

Quote:

midori:~# ip a l

```
2: lo: <LOOPBACK,UP> mtu 16436 qdisc noqueue
  link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
  inet 127.0.0.1/8 scope host lo
4: eth0: <BROADCAST,MULTICAST,UP> mtu 1500 qdisc pfifo_fast qlen 1000
  link/ether 00:05:1c:19:67:f4 brd ff:ff:ff:ff:ff:ff
  inet xxx/19 brd 255.255.255.255 scope global eth0
6: eth1: <BROADCAST,MULTICAST,UP> mtu 1500 qdisc pfifo_fast qlen 1000
  link/ether 00:05:1c:03:26:36 brd ff:ff:ff:ff:ff:ff
  inet 192.168.0.210/24 brd 192.168.0.255 scope global eth1
3: venet0: <BROADCAST,POINTOPOINT,NOARP,UP> mtu 1500 qdisc noqueue
  link/void
```

midori:~# ip r l

```
192.168.0.5 dev venet0 scope link src xxx
192.168.0.0/24 dev eth1 proto kernel scope link src 192.168.0.210
83.213.128.0/19 dev eth0 proto kernel scope link src xxx
default via 83.213.128.1 dev eth0
```

Regards,

--

Santi Saez
