
Subject: [PATCH 8/11 net-2.6.26] [INET]: uc_ttl assignment in
inet_csk_ctl_sock_create is extra.

Posted by [den](#) on Fri, 28 Mar 2008 09:08:55 GMT

[View Forum Message](#) <> [Reply to Message](#)

uc_ttl is initialized in inet(6)_create and never changed except exact
setsockopt ioctl. Remove it.

Signed-off-by: Denis V. Lunev <den@openvz.org>

net/ipv4/inet_connection_sock.c | 1 -

1 files changed, 0 insertions(+), 1 deletions(-)

diff --git a/net/ipv4/inet_connection_sock.c b/net/ipv4/inet_connection_sock.c

index 2cb3552..bfa6274 100644

--- a/net/ipv4/inet_connection_sock.c

+++ b/net/ipv4/inet_connection_sock.c

@@ -660,7 +660,6 @@ int inet_csk_ctl_sock_create(struct sock **sk, unsigned short family,
if (rc == 0) {

 *sk = socket->sk;

 (*sk)->sk_allocation = GFP_ATOMIC;

- inet_sk(*sk)->uc_ttl = -1;

/*

 * Unhash it so that IP input processing does not even see it,

 * we do not wish this socket to see incoming packets.

--

1.5.3.rc5

Containers mailing list

Containers@lists.linux-foundation.org

<https://lists.linux-foundation.org/mailman/listinfo/containers>
