
Subject: [RFC][PATCH 4/4] PID: use the target ID specified in procfs
Posted by [Nadia Derby](#) on Fri, 28 Mar 2008 09:53:13 GMT
[View Forum Message](#) <> [Reply to Message](#)

[PATCH 04/04]

This patch makes use of the target ids specified by a previous write to /proc/self/next_id as the ids to use to allocate the next upid nrs. Upper levels upid nrs that are not specified in next_pids file are left to the kernel choice.

Signed-off-by: Nadia Derby <Nadia.Derbey@bull.net>

include/linux/pid.h | 2
kernel/fork.c | 3 -
kernel/pid.c | 141 ++++++-----
3 files changed, 126 insertions(+), 20 deletions(-)

Index: linux-2.6.25-rc3-mm1/include/linux/pid.h

=====
--- linux-2.6.25-rc3-mm1.orig/include/linux/pid.h 2008-03-28 08:18:53.000000000 +0100
+++ linux-2.6.25-rc3-mm1/include/linux/pid.h 2008-03-28 08:21:19.000000000 +0100
@@ -119,7 +119,7 @@ extern struct pid *find_get_pid(int nr);
extern struct pid *find_ge_pid(int nr, struct pid_namespace *);
int next_pidmap(struct pid_namespace *pid_ns, int last);

-extern struct pid *alloc_pid(struct pid_namespace *ns);
+extern struct pid *alloc_pid(struct pid_namespace *ns, int *retval);
extern void free_pid(struct pid *pid);

/*

Index: linux-2.6.25-rc3-mm1/kernel/fork.c

=====
--- linux-2.6.25-rc3-mm1.orig/kernel/fork.c 2008-03-28 08:18:53.000000000 +0100
+++ linux-2.6.25-rc3-mm1/kernel/fork.c 2008-03-28 08:21:19.000000000 +0100
@@ -1199,8 +1199,7 @@ static struct task_struct *copy_process(
goto bad_fork_cleanup_io;

if (pid != &init_struct_pid) {
- retval = -ENOMEM;
- pid = alloc_pid(task_active_pid_ns(p));
+ pid = alloc_pid(task_active_pid_ns(p), &retval);
if (!pid)
goto bad_fork_cleanup_io;

Index: linux-2.6.25-rc3-mm1/kernel/pid.c

=====

```

--- linux-2.6.25-rc3-mm1.orig/kernel/pid.c 2008-03-28 08:18:53.000000000 +0100
+++ linux-2.6.25-rc3-mm1/kernel/pid.c 2008-03-28 08:21:19.000000000 +0100
@@ -122,6 +122,26 @@ static void free_pidmap(struct upid *upi
    atomic_inc(&map->nr_free);
}

+static inline int alloc_pidmap_page(struct pidmap *map)
+{
+ if (unlikely(!map->page)) {
+ void *page = kzalloc(PAGE_SIZE, GFP_KERNEL);
+ /*
+  * Free the page if someone raced with us
+  * installing it:
+  */
+ spin_lock_irq(&pidmap_lock);
+ if (map->page)
+ kfree(page);
+ else
+ map->page = page;
+ spin_unlock_irq(&pidmap_lock);
+ if (unlikely(!map->page))
+ return -1;
+ }
+ return 0;
+}
+
static int alloc_pidmap(struct pid_namespace *pid_ns)
{
    int i, offset, max_scan, pid, last = pid_ns->last_pid;
@@ -134,21 +154,8 @@ static int alloc_pidmap(struct pid_names
    map = &pid_ns->pidmap[pid/BITS_PER_PAGE];
    max_scan = (pid_max + BITS_PER_PAGE - 1)/BITS_PER_PAGE - !offset;
    for (i = 0; i <= max_scan; ++i) {
- if (unlikely(!map->page)) {
- void *page = kzalloc(PAGE_SIZE, GFP_KERNEL);
- /*
-  * Free the page if someone raced with us
-  * installing it:
-  */
- spin_lock_irq(&pidmap_lock);
- if (map->page)
- kfree(page);
- else
- map->page = page;
- spin_unlock_irq(&pidmap_lock);
- if (unlikely(!map->page))
- break;
- }

```

```

+ if (unlikely(alloc_pidmap_page(map)))
+ break;
+ if (likely(atomic_read(&map->nr_free))) {
+ do {
+ if (!test_and_set_bit(offset, map->page)) {
@@ -182,6 +189,35 @@ static int alloc_pidmap(struct pid_names
+ return -1;
+ }

+/*
+ * Return a predefined pid value if successful (ID_AT(pid_l, level)),
+ * -errno else
+ */
+static int alloc_fixed_pidmap(struct pid_namespace *pid_ns,
+ struct sys_id *pid_l, int level)
+{
+ int offset, pid;
+ struct pidmap *map;
+
+ pid = ID_AT(pid_l, level);
+ if (pid < RESERVED_PIDS || pid >= pid_max)
+ return -EINVAL;
+
+ map = &pid_ns->pidmap[pid / BITS_PER_PAGE];
+
+ if (unlikely(alloc_pidmap_page(map)))
+ return -ENOMEM;
+
+ offset = pid & BITS_PER_PAGE_MASK;
+ if (test_and_set_bit(offset, map->page))
+ return -EBUSY;
+
+ atomic_dec(&map->nr_free);
+ pid_ns->last_pid = max(pid_ns->last_pid, pid);
+
+ return pid;
+}
+
+int next_pidmap(struct pid_namespace *pid_ns, int last)
+{
+ int offset;
@@ -243,20 +279,91 @@ void free_pid(struct pid *pid)
+ call_rcu(&pid->rcu, delayed_put_pid);
+ }

-struct pid *alloc_pid(struct pid_namespace *ns)
+/*
+ * Called by alloc_pid() to use a list of predefined ids for the calling

```

```

+ * process' upper ns levels.
+ * Returns next pid ns to visit if successful (may be NULL if walked through
+ * the entire pid ns hierarchy).
+ * i is filled with next level to be visited (useful for the error cases).
+ */
+static struct pid_namespace *set_predefined_pids(struct pid_namespace *ns,
+ struct pid *pid,
+ struct sys_id *pid_l,
+ int *next_level)
+{
+ struct pid_namespace *tmp;
+ int rel_level, i, nr;
+
+ rel_level = pid_l->nids - 1;
+ if (rel_level > ns->level)
+ return ERR_PTR(-EINVAL);
+
+ tmp = ns;
+
+ /*
+ * Use the predefined upid nrs for levels ns->level down to
+ * ns->level - rel_level
+ */
+ for (i = ns->level ; rel_level >= 0; i--, rel_level--) {
+ nr = alloc_fixed_pidmap(tmp, pid_l, rel_level);
+ if (nr < 0) {
+ tmp = ERR_PTR(nr);
+ goto out;
+ }
+
+ pid->numbers[i].nr = nr;
+ pid->numbers[i].ns = tmp;
+ tmp = tmp->parent;
+ }
+
+ id_blocks_free(pid_l);
+
+out:
+ *next_level = i;
+ return tmp;
+}
+
+struct pid *alloc_pid(struct pid_namespace *ns, int *retval)
+{
+ struct pid *pid;
+ enum pid_type type;
+ int i, nr;
+ struct pid_namespace *tmp;

```

```

    struct upid *upid;
+ struct sys_id *pid_l;

+ *retval = -ENOMEM;
    pid = kmem_cache_alloc(ns->pid_cache, GFP_KERNEL);
    if (!pid)
        goto out;

    tmp = ns;
- for (i = ns->level; i >= 0; i--) {
+ i = ns->level;
+
+ /*
+  * If there is a list of upid nrs specified, use it instead of letting
+  * the kernel chose the upid nrs for us.
+  */
+ pid_l = current->next_id;
+ if (pid_l && pid_l->nids) {
+ /*
+  * returns the next ns to be visited in the following loop
+  * (or NULL if we are done).
+  * i is filled in with the next level to be visited. We need
+  * it to undo things in the error cases.
+  */
+ tmp = set_predefined_pids(ns, pid, pid_l, &i);
+ if (IS_ERR(tmp)) {
+     *retval = PTR_ERR(tmp);
+     goto out_free;
+ }
+ }
+
+ *retval = -ENOMEM;
+ /*
+  * Let the lower levels upid nrs be automatically allocated
+  */
+ for ( ; i >= 0; i--) {
    nr = alloc_pidmap(tmp);
    if (nr < 0)
        goto out_free;

--

```

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
